

Philips Signage Solutions Q-Line Display

55"Direct LED Backlight Ultra HD

SignageSolutions



55BDL3650Q

Stand out from the crowd

Your versatile and easy-to-set-up 18/7 display

Inform and enthral with a Philips Q-Line 4K Ultra HD digital display. This reliable, easy-to-install, Android-powered signage solution is Wave-ready for remote management, putting you in full control, any time, anywhere.

Effortless setup. Total control.

- Optional Interact for wireless screen share
- Catch the Wave for revolutionary results

Cost-effective system solution

- Easy control. Remotely manage networked displays
- Easily schedule content from a USB or internal memory

Smart and powerful

- · Connect and control your content via the cloud
- · Android SoC processor. Native and web apps
- WiFi connection made easy with an optional CRD22 module

Versatile system solution

- Ultra-HD. Rich images. Stunning contrast
- FailOver. Ensure your display never goes blank



Specifications

Picture/Display

- Diagonal screen size: 54.6 inch / 138.7 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 400 cd/m²
- Contrast ratio (typical): 1300:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 9 ms
- Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 0.315 x 0.315 mm
- Display colours: 1.07 Billion
- Operating system: Android 10
- Panel technology: ADS
- Picture enhancement: 3/2 2/2 motion pull down, Dynamic contrast enhancement, Progressive scan
- Haze: 2%

Supported Display Resolution

Computer formats

Resolution	Refresh rate
1920 x 1080	60 Hz
1600 x 1200	60 Hz
1440 × 900	60 Hz
1280 x 1024	60 Hz
1280×720	60 Hz
1280×800	60 Hz
1024×768	60, 70, 75 Hz
1680 x 1050	60 Hz
3840 x 2160	60 Hz

Video formats

Resolution Refresh rate 1080p 50, 60 Hz 1080i 50, 60 Hz 720p 50,60 Hz 2160p 50, 60 Hz

Connectivity

- Video input: HDMI 2.0 (x 2), USB 2.0 (x 2), DVI-I (x 1), USB 3.0 (x1)
- Audio input: 3.5 mm jack
- Audio output: 3.5 mm jack
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack
- Other connections: micro SD

Convenience

- Energy-saving functions: Smart Power
- Tiled Matrix: Up to 3 x 3
- Keyboard control: Lockable, Hidden
- Network controllable: RS232, RJ45
- · Signal loop through: RS232, IR Loop through

- Placement: Landscape (18/7), Portrait (18/7)
- · Remote control signal: Lockable

Dimensions

- Bezel width: 13.9 mm (Even bezel)
- Set dimensions (W x H x D): 1241.8 x 712.6 x 63.6 mm
- Set dimensions in inch (W x H x D): 48.89 x 28.06 x 2.50 inch
- Wall Mount: 400 mm x 400 mm, M6
- Product weight: 16.6 kg
- Product weight (lb): 36.60 lb

Operating conditions

- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): $-20 \sim 60$ °C MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20~80% RH (No condensation)
- Humidity range (storage) [RH]: 5~95% RH (No condensation)
- Altitude: 0 ~ 3000 m

Power

- Mains power: 100 ~ 240 VAC
- Standby power consumption: <0.5 W
- Consumption (Max): 200 W
- Consumption (Typical): 130 W
- Power Saving Features: Smart Power
- · Energy Label Class: G

Sound

• Built-in speakers: 2 x 10 W RMS

Multimedia Applications

- USB Playback Video: MPEG, H.264, H.263, H.265, AVI, MP4, VP8
- USB Playback Picture: JPEG, BMP, PNG
- USB Playback Audio: AAC, HEAAC, MPEG

Accessories

 Included Accessories: IR sensor cable (1.8 m) (x 1), RS232 daisy-chain cable, Philips logo (x 1), AC Power Cord, AC Switch Cover, Quick start guide, Remote control and AAA batteries, RS232 cable, USB cover and screws, Wire Clamper (x 3)

Miscellaneous

- Warranty: 3 year warranty
- On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese, Spanish, Traditional Chinese, Arabic,

Highlights

SJapanes Prowser

Chegulatanydappmovallyc@EcoBetif@@aChesslend@@th theoinGegetted HTML5 browser. Using the Chromium-based browser, design your content britinerand Polanicat either a single display or your டீ இந்த மாக்கியை வெல்லைக்கொர் in both landscape ar இந்த நடித்த நடித்த மாக்கிய மாகம் பார் மாக்கிய ம

FailOver

Critical for demanding commercial applications, FailOver is a revolutionary technology that automatically plays back-up content onscreen in the unlikely event of an input source or application failure. Simply select a primary input connection and a FailOver connection and you are ready for instant content protection.

Integrated media player

Easily schedule content to play from a USB or from internal memory. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

Interact (optional)

Wirelessly screen share using your existing Wi-Fi network to instantly and securely connect devices, or use our optional HDMI Interact dongle to cast directly onto the screen without connecting into the secured network.

Powered by Android 10

Powered by our Android 10 SoC platform, these hardworking Philips professional displays are optimised for native Android apps, and you can install web apps directly onto the display too. Flexible and secure, ensuring display specs stay up to the moment for longer.

PPDS Wave

Unlock the power, versatility and intelligence inside your Philips Q-Line displays remotely with Wave. This evolutionary cloud platform puts you fully in control, with simplified installation and setup, monitoring and controlling displays, upgrading firmware, managing playlists and setting power schedules. Saving you time, energy and environmental impact.













Issue date 2023-08-16

© 2023 Koninklijke Philips N.V. All Rights reserved.

Version: 2.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 86383 EAN: 87 12581 79931 1

www.philips.com