

# AVOCOR E SERIES DATASHEET

55" | 65" | 75" | 86"



## **OVERVIEW**

The new and improved E40 series displays utilize the very latest optimized touch technology, that supports up to 20 points of touch using Avocor Intelligent Touch, and superior optically bonded glass technology providing a smooth and extremely accurate, low latency writing experience as well as object recognition.

The ability to easily switch between using a pen, finger, and palm create for a fluid collaborative environment for users in real-time, with an array of front-facing guest connectivity options now including a Type-C connection along the Connect and Control bar, and features Avocor's UiQ touch enabled interface.

IDEAL FOR:







# **SOLUTION**

### Highlights



Avocor UiQ - smart touch enabled dynamic user interface.



FUSE - cloud-based display & software management platform for IT Managers.



Superior glass technology provides an extremely accurate writing experience.



Zero parallax optically bonded glass surface for pixel-perfect inking.



Type-C connectivity and enhanced HDMI out supporting 4K video @60Hz.



Front-facing 40W soundbar delivering a crystal-clear audio experience.



#### **SPECIFICATIONS**

| DISPLAY                    | AVE-5540                                                                                                                      | AVE-6540                                                                  | AVE-7540                                               | AVE-8640                                              |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------------|-------------------------------------------------------|
| Diagonal size (Inch)       | 55                                                                                                                            | 65                                                                        | 75                                                     | 86                                                    |
| Backlight                  | Direct-lit LED                                                                                                                |                                                                           |                                                        |                                                       |
| spect ratio                | 16:9                                                                                                                          |                                                                           |                                                        |                                                       |
| Resolution                 | 3840 x 2160 @ 60Hz                                                                                                            |                                                                           |                                                        |                                                       |
| lesponse time              | 8 ms                                                                                                                          |                                                                           |                                                        |                                                       |
| Brightness                 | 400 (cd/m2)                                                                                                                   |                                                                           |                                                        |                                                       |
| Contrast ratio             | 4000:1                                                                                                                        |                                                                           |                                                        |                                                       |
| /iewing angle              | 178°/178°                                                                                                                     |                                                                           |                                                        |                                                       |
| Supported colors           | 10 Bit 1.07 Billion Color                                                                                                     |                                                                           |                                                        |                                                       |
| Display orientation        |                                                                                                                               | Lands                                                                     | cape                                                   |                                                       |
| TOUCH SYSTEM               |                                                                                                                               |                                                                           |                                                        |                                                       |
| nterface                   | 1 x Type-C, 2 x USB-B (1 x 2.0 +1 x 3.0)                                                                                      |                                                                           |                                                        |                                                       |
| Fouch                      | Up to 20 Point Avocor Intelligent Touch - supports 1 x fine tip stylus                                                        |                                                                           |                                                        |                                                       |
| Glass                      | Zero parallax, bonded, anti-fingerprint glass                                                                                 |                                                                           |                                                        |                                                       |
| Supported operating system |                                                                                                                               | Windows 8 / 10; Mac C                                                     | DSX*; Linux*; Chrome                                   |                                                       |
| CONNECTIVITY               |                                                                                                                               |                                                                           |                                                        |                                                       |
| Guest inputs               | 1 x Type-C (45W PD), 1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 3.0 Hub                                                         |                                                                           |                                                        |                                                       |
| Side IO                    | 2 x HDMI 2.0, 1 x DisplayPort 1.2, 1 x USB-B Touch, 1 x USB-A 3.0 Hub, 1 x USB-A Service Port, 1 x HDMI Out (Support 4K@60Hz) |                                                                           |                                                        |                                                       |
| Audio                      | 1 x 3.5mm audio out, 1 x optical (SPDIF)                                                                                      |                                                                           |                                                        |                                                       |
| Control                    | 1 x RS-232, 1 x LAN Ethernet (RJ-45) in, 1 x LAN Ethernet (RJ-45) out                                                         |                                                                           |                                                        |                                                       |
| OPS slot                   |                                                                                                                               | Yes, 3840 x 2                                                             | 160@60Hz                                               |                                                       |
| AUDIO & MICROPHONE         |                                                                                                                               |                                                                           |                                                        |                                                       |
| Built-in speakers          | 2 x 20W - forward facing                                                                                                      |                                                                           |                                                        |                                                       |
| DISPLAY & REMOTE FUNCTI    | ONS                                                                                                                           |                                                                           |                                                        |                                                       |
| Auto-source-detection      | Yes                                                                                                                           |                                                                           |                                                        |                                                       |
| Source preview             | Yes                                                                                                                           |                                                                           |                                                        |                                                       |
| Blank                      | Yes                                                                                                                           |                                                                           |                                                        |                                                       |
| reeze                      | Yes                                                                                                                           |                                                                           |                                                        |                                                       |
| PHYSICAL SPECIFICATIONS    |                                                                                                                               |                                                                           |                                                        |                                                       |
| Product dimensions         | 1286 x 802 x 78.4 mm<br>50.63 x 31.57 x 3.09 in                                                                               | 1513 x 938 x 99.5 mm<br>59.57 x 36.93 x 3.92 in                           | 1735 x 1062 x 91 mm<br>68.31 x 41.81 x 3.58 in         | 1981 x 1201 x 91 mm<br>77.99 x 47.28 x 3.58 in        |
| Shipping dimensions        | 1421 x 932 x 216 mm<br>55.94 x 43.70 x 8.50 in                                                                                | 1649 x 1110 x 216 mm<br>64.92 x 43.70 x 8.50 in                           | 1886 x 1210 x 227 mm<br>74.25 x 47.64 x 8.94 in        | 2130 x 1375 x 250 mm<br>83.86 x 54.13 x 9.84 in       |
| Weight                     | Net: 28 kgs   61.73 lbs<br>Gross: 41 kgs   90.39 lbs                                                                          | Net: 39 kgs   85.98 lbs<br>Gross: 52 kgs   114.64 lbs                     | Net: 52 kgs   114.64 lbs<br>Gross: 64 kgs   141.10 lbs | Net: 66 kgs   145.51 lbs<br>Gross: 81 kgs   178.57 lb |
| Wall mount (VESA)          | 400 x 400 mm   15.75 x 15.75 in                                                                                               | 600 x 400 mm   23.62 x 15.75 in                                           | 800 x 400 mm                                           | 31.50 x 15.75 in                                      |
| PC Mount                   |                                                                                                                               | 100 x 100 mm                                                              | 3.94 x 3.94 in                                         |                                                       |
| Handles                    |                                                                                                                               | 2                                                                         |                                                        | 4                                                     |
| POWER                      |                                                                                                                               |                                                                           |                                                        |                                                       |
| Power supply               | AC100-240V (worldwide), 50/60Hz                                                                                               |                                                                           |                                                        |                                                       |
| Max power consumption      | <220W <340W <520W                                                                                                             |                                                                           |                                                        |                                                       |
| Standby                    | ≤0.5W                                                                                                                         |                                                                           |                                                        |                                                       |
| ENVIRONMENTAL              |                                                                                                                               |                                                                           |                                                        |                                                       |
| Operating temperature      |                                                                                                                               | 0°C ~ 4                                                                   | <br>4∩°C                                               |                                                       |
| Storage temperature        | -20°C ~ 60°C                                                                                                                  |                                                                           |                                                        |                                                       |
| Humidity                   | 20% ~ 85%                                                                                                                     |                                                                           |                                                        |                                                       |
|                            |                                                                                                                               | 2070                                                                      | ··                                                     |                                                       |
| WHAT COMES IN THE DOV      |                                                                                                                               |                                                                           |                                                        |                                                       |
| WHAT COMES IN THE BOX      | 1 y Pomoto control C battari 2                                                                                                | v 2mm fino-tip passive to ush at ili-                                     | oc AC nower cords (1 v.LII/ 1 ·· F                     | THE AVERS A VALUE AVER TO                             |
| WHAT COMES IN THE BOX      |                                                                                                                               | x 3mm fine-tip passive touch stylus<br>118.1 in), 1 x HDMI cable (3m   11 |                                                        |                                                       |



www.avocor.com















Upgrade your solution with:



GroupShare Secure and simple one-touch access to your apps

Avocor OPS Seamless interoperability with Avocor displays. **Austere Clean** & Protect

Additional remote

Additional stylus

**Avocor Mobile** Stand