

Key **Features**

- Easily extend your content from laptops and mobile devices
- USB-C one-cable solution for audiovisual and power signal transmission
- Flexible display setup work at any angle
- Compact size, light weight, and highly portable
- Endurable one-piece design



Product **Description**

The ViewSonic VA1655 is a portable 16" Full HD monitor perfect for overcoming one-screen limitations outside the office. Extend the screen from phones, tablets, or laptops for mobile work, one-on-one presentations, or leisure entertainment. The two universal USB Type C connectors provide a one-cable solution for audiovisual and power signal transmission. The adjustable stand and pivot-able display will support your working angles.



- 1. USB Type C(Power)x1 2. USB Type C x1 3. Mini HDMI 4. Audio Out 5. Joy Key

Visit Us

www.viewsonic.com



DISPLAY		WEIGHT (IMPERIAL)	
Display Size (in.):	16	Net (lbs):	1.5
Viewable Area (in.):	15.6	Net Without Stand (lbs):	1.5
Panel Type:	IPS Technology	Gross (lbs):	3.7
Resolution:	1920 x 1080	WEIGHT (METRIC)	
Resolution Type:	FHD (Full HD)	Net (kg):	0.7
Static Contrast Ratio:	800:1 (typ)	Net Without Stand (kg):	0.7
Dynamic Contrast Ratio:	50M:1	Gross (kg):	1.7
Light Source:	LED	DIMENSIONS (IMPERIAL) (WX	(HXD)
Brightness:	250 cd/m² (typ)	Packaging (in.):	17.1 x 15.4 x 3.5
Colors:	16.2M	Physical (in.):	14.1 x 8.9 x 0.7
Color Space Support:	8 bit (6 bit + FRC)	Physical Without Stand (in.):	14.1 x 8.9 x 0.7
Aspect Ratio:	16:9	DIMENSIONS (METRIC) (WXH	XD)
Response Time (Typical GTG):	7ms	Packaging (mm):	434 x 391 x 88
		Physical (mm):	359 x 227 x 17
Viewing Angles:	170° horizontal, 170° vertical	Physical Without Stand (mm):	359 x 227 x 17
Backlight Life (Hours):	15000 Hrs (Min)	GENERAL	
Curvature:	Flat		cTUVus, FCC-B, ICES003, Energy
Refresh Rate (Hz):	60	Regulations:	Star, EPEAT, CEC, NRCan, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKrSEPRO, UKCA, BSMI, VCCI, PSE, BIS
Blue Light Filter:	Yes		
Color Gamut:	NTSC: 45% size (Typ) sRGB: 64% size (Typ)		
Pixel Size:	0.179 mm (H) x 0.179 mm (V)		VA1655 x1, mini HDMI to HDMI Cab
Surface Treatment:	Anti-Glare, Hard Coating (3H)	PACKAGE CONTENTS:	(v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1, Sleeve case x1
COMPATIBILITY	, in clare, mara coating (em,		
PC Resolution (max):	1920x1080	Recycle/Disposal:	Please dispose of in accordance wit local, state or federal laws.
Mac® Resolution (max):	1920x1080		*Warranty offered may differ from
mace resolution (max).	Windows 10/11 certified; macOS	Warranty:	market to market
PC Operating System:	tested	Country Of Origin:	144
Mac® Resolution (min):	1920×1080	Power Management:	Energy Star standards, EPEAT
CONNECTOR			
USB 3.2 Type C DisplayPort Alt mode only :	1 (60W power charger)		
3.5mm Audio Out:	1		
Mini HDMI:	1		
Power in:	USB Type C (power only)		
AUDIO			
Internal Speakers:	0.8Watts x2		
POWER			
Eco Mode (Conserve):	5.1W		
Eco Mode (optimized):	6W		
Consumption (typical):	7W		
Consumption (max):	7.3W		
Voltage:	DC 5V/9V/12V/15V/20V		
Stand-by:	0.3W		
Power Supply:	External (Optional)		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	Up, Right, Down, Left, Power		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual		
	Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
INPUT SIGNAL			
Frequency Horizontal:	mini HDMI (v1.4): 15 ~ 82KHz, Type C: 24 ~ 82KHz		
Frequency Vertical:	mini HDMI (v1.4): 50 ~ 75Hz, Type C: 50 ~ 75Hz		
VIDEO INPUT			
Digital Sync:	TMDS - mini HDMI (v1.4), Micro- Packet - Type C		
ERGONOMICS			
Tilt (Forward/Back):	30° / 53°		
(

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.