



LCD DISPLAY

VA3209-2K-MHD


Key Features

- SuperClear® IPS panel
- QHD 2560 X 1440 resolution
- HDMI and DisplayPort inputs for flexible connectivity
- HDR10 delivers Stellar Contrast and Color Accuracy
- 75hz Variable Refresh Rate eliminates screen tearing and reduces stuttering



Product Description

The ViewSonic VA3209-2K-MHD is a 32" 2K monitor featuring HDMI and DisplayPort inputs for business and home use. With a 32" display and 2560 X 1440 resolution that delivers larger and clearer images, the QHD monitor expands your productivity. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through adaptive sync, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.



1. Menu Control Panel
2. DC In
3. HDMI*2
4. Display Port
5. Audio Out
6. VESA Compatible (Wall Mount 100x100mm)

7. Speakers

Visit Us

www.viewsonic.com

DISPLAY

| | |
|-----------------------------------|---|
| Display Size (in.): | 32 |
| Viewable Area (in.): | 31.5 |
| Panel Type: | IPS Technology |
| Resolution: | 2560 x 1440 |
| Resolution Type: | QHD (Quad HD) |
| Static Contrast Ratio: | 1,200:1 (typ) |
| Dynamic Contrast Ratio: | 50M:1 |
| Light Source: | LED |
| Brightness: | 250 cd/m ² (typ) |
| Colors: | 1,07B |
| Color Space Support: | 10 bit (8 bit + FRC) |
| Aspect Ratio: | 16:9 |
| Response Time (Typical GTG): | 4ms |
| Viewing Angles: | 178° horizontal, 178° vertical |
| Backlight Life (Hours): | 30000 Hrs (Min) |
| Curvature: | Flat |
| Refresh Rate (Hz): | 75 |
| Variable Refresh Rate Technology: | Yes |
| Blue Light Filter: | Yes |
| Flicker-Free: | Yes |
| Color Gamut: | NTSC: 72% size (Typ) sRGB: 104% size (Typ) |
| Pixel Size: | 0.273 mm (H) x 0.273 mm (V) |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) |

COMPATIBILITY

| | |
|------------------------|---------------------------------------|
| PC Resolution (max): | 2560x1440 |
| Mac® Resolution (max): | 2560x1440 |
| PC Operating System: | Windows 10/11 certified; macOS tested |
| Mac® Resolution (min): | 2560x1440 |

CONNECTOR

| | |
|------------------|-----------------------------|
| 3.5mm Audio Out: | 1 |
| HDMI 1.4: | 2 |
| DisplayPort: | 1 |
| Power in: | DC Socket (Center Positive) |

AUDIO

| | |
|--------------------|-------------|
| Internal Speakers: | 2.5Watts x2 |
|--------------------|-------------|

POWER

| | |
|------------------------|------------------------|
| Eco Mode (Conserve): | 22W |
| Eco Mode (optimized): | 26W |
| Consumption (typical): | 30W |
| Consumption (max): | 35W |
| Voltage: | AC 100-240V |
| Stand-by: | 0.5W |
| Power Supply: | External Power Adaptor |

ADDITIONAL HARDWARE

| | |
|-----------------------|---|
| Kensington Lock Slot: | 1 |
|-----------------------|---|

CONTROLS

| | |
|--------------------|---|
| Physical Controls: | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) |
| On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |

OPERATING CONDITIONS

| | |
|----------------------------|-----------------------------|
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90% |

WALL MOUNT

| | |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

INPUT SIGNAL

| | |
|-----------------------|-------------|
| Frequency Horizontal: | 15 ~ 120KHz |
| Frequency Vertical: | 24 ~ 75Hz |

VIDEO INPUT

| | |
|---------------|--|
| Digital Sync: | TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4) |
|---------------|--|

ERGONOMICS

| | |
|----------------------|-----------|
| Tilt (Forward/Back): | -5° / 20° |
|----------------------|-----------|

WEIGHT (IMPERIAL)

| | |
|--------------------------|------|
| Net (lbs): | 15 |
| Net Without Stand (lbs): | 12.3 |
| Gross (lbs): | 20.3 |

WEIGHT (METRIC)

| | |
|-------------------------|-----|
| Net (kg): | 6.8 |
| Net Without Stand (kg): | 5.6 |
| Gross (kg): | 9.2 |

DIMENSIONS (IMPERIAL) (WXHXD)

| | |
|-------------------------------|-------------------|
| Packaging (in.): | 30.3 x 20.1 x 4.9 |
| Physical (in.): | 28.1 x 20.5 x 9.1 |
| Physical Without Stand (in.): | 28.1 x 16.8 x 2.3 |

DIMENSIONS (METRIC) (WXHXD)

| | |
|------------------------------|-----------------|
| Packaging (mm): | 770 x 510 x 125 |
| Physical (mm): | 714 x 520 x 231 |
| Physical Without Stand (mm): | 714 x 428 x 59 |

GENERAL

| | |
|--------------|--|
| Regulations: | CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, BIS |
|--------------|--|

| | |
|-------------------|---|
| PACKAGE CONTENTS: | VA3209-2K-MHD x1, HDMI Cable (v2.0; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 |
|-------------------|---|

| | |
|-------------------|--|
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
|-------------------|--|

| | |
|-----------|--|
| Warranty: | *Warranty offered may differ from market to market |
|-----------|--|