

# ViewSonic® LCD DISPLAY VG3209-4K

## Key Features

- 4K UHD 3840 x 2160 resolution
- SuperClear® IPS panel
- Height-adjustable swivel stand with tilt function
- HDMI and Display Port inputs for simple connectivity
- HDR10 Delivers Stellar Contrast



## Product Description

The ViewSonic VG3209-4K is a 32" UHD monitor featuring HDMI and Display Port inputs for business and home use. The eye-care technology presets to cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)



**DISPLAY**

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	350 cd/m <sup>2</sup> (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + A-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 91% size (Typ) sRGB: 128% size / 99% coverage (Typ)
Pixel Size:	0.182 mm (H) x 0.182 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

**CONNECTOR**

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	2
Power in:	DC Socket (Center Positive)

**AUDIO**

Internal Speakers:	2.5Watts x2
--------------------	-------------

**POWER**

Eco Mode (Conserve):	25W
Eco Mode (optimized):	33W
Consumption (typical):	40W
Consumption (max):	42W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
Cable Organization:	Yes

**CONTROLS**

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	HDMI (v2.0): 15 ~ 140KHz, DisplayPort (v1.4): 24 ~ 140KHz
Frequency Vertical:	HDMI (v2.0): 24 ~ 75Hz, DisplayPort (v1.4): 48 ~ 75Hz

**VIDEO INPUT**

Digital Sync:	TMDs - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

**ERGONOMICS**

Height Adjust (mm):	90
Swivel:	360°
Tilt (Forward/Back):	-4° / 20°

**WEIGHT (IMPERIAL)**

Net (lbs):	19.6
Net Without Stand (lbs):	14.8
Gross (lbs):	24

**WEIGHT (METRIC)**

Net (kg):	8.9
Net Without Stand (kg):	6.7
Gross (kg):	10.9

**DIMENSIONS (IMPERIAL) (WXHXD)**

Packaging (in.):	34.1 x 19.8 x 5.7
Physical (in.):	28.1 x 18.47~22.01 x 7.9
Physical Without Stand (in.):	28.1 x 16.8 x 2.3

**DIMENSIONS (METRIC) (WXHXD)**

Packaging (mm):	865 x 503 x 144
Physical (mm):	714 x 469~559 x 202
Physical Without Stand (mm):	714 x 428 x 59

**GENERAL**

Regulations:	Energy Star, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA
PACKAGE CONTENTS:	VG3209-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0: Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards