

Key **Features**

- **OLED TECH:** True Black with 1.07 Billion colours (10Bit)
- Real and Surreal: 100% DCI-P3 Pantone
 Validated colour coverage with Delta E < 2 as colour quality guarantee
- Create Anywhere You Want: Tripod ready and foldable stand for outdoor shooting and indoor review
- Instant View: Camera ready (Micro HDMI)
 and USB-C charging that brings your creative
 workstation wherever you are
- Integrated hood: Foldaway hood attaches instantly when you need to eliminate ambient light



Product **Description**

Introducing industry-leading VP16-OLED with 1.07 Billion colours (10Bit). Merging what's real with the surreal, it boasts 100 % DCI-P3 Pantone Validated colour coverage with Delta E < 2 as the colour quality guarantee. Tripod-ready, VP16-OLED comes equipped with a foldable stand allowing you to perform your best in both indoor and outdoor settings. "Go dark" at any moment with a foldaway attachable hood that instantly eliminates any ambient light. Take your creative workstation no matter where you go and review the immediate results of your work, connecting your camera to the VP16-OLED via Micro HDMI and charging it effortlessly through USB-C connectivity.

Visit Us

www.viewsonic.com

16.3 x 12.3 x 3.5 14.1 x 8.92~12.38 x 0.8 14.1 x 8.9 x 0.2

415 x 312 x 90

359 x 227 x 6

359 x 226.682~314.48 x 19

cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCan, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UKrSEPRO, UKCA, BSMI, BIS

VP16-OLED x1, micro HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C to Type-A 3.2 Gen1 Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Hood x1

Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from market to market Energy Star standards, EPEAT

3	VP16-	OLED 15.6" OLED Portable	e Monito
DISPLAY		WEIGHT (IMPERIAL)	
Display Size (in.):	16	Net (lbs):	2.2
Viewable Area (in.):	15.6	Net Without Stand (lbs):	2.2
Panel Type:	OLED Technology	Gross (lbs):	4.8
Resolution:	1920 x 1080	WEIGHT (METRIC)	
Resolution Type:	FHD (Full HD)	Net (kg):	0.98
Static Contrast Ratio:	100,000:1 (typ)	Net Without Stand (kg):	0.98
Dynamic Contrast Ratio:	20M:1	Gross (kg):	2.2
Brightness:	400 cd/m² (typ)	DIMENSIONS (IMPERIAL) (V	
Colors:	1.07B	Packaging (in.):	16.3 x
Color Space Support:	10 bit (8 bit + FRC)	Physical (in.):	14.1 x
Aspect Ratio:	16:9	Physical Without Stand (in.):	14.1 x
Response Time (Typical Tr+Tf):	1ms	DIMENSIONS (METRIC) (WX	-
Viewing Angles:	170° horizontal, 170° vertical	Packaging (mm):	415 x
Backlight Life (Hours):	N/A Hrs (Min)	Physical (mm):	359 x
Curvature:	Flat	Physical Without Stand (mm):	359 x
Refresh Rate (Hz):	60	GENERAL	•TUV/
Blue Light Filter:	Yes Adobe RGB: 112% size / 96% coverage (Typ) DCI-P3: 111% size / 100% coverage	Regulations:	cTUVu Star, E Mexico RoHS, UkrSE
Color Gamut:	(Typ) EBU: 149% size / 100% coverage (Typ) REC709: 150% size / 100% coverage (Typ) SMPTE-C: 163% size / 100% coverage (Typ)	PACKAGE CONTENTS:	VP16- (v1.4; Cable Type-A x1, AC Guide
	NTSC: 107% size (Typ) sRGB: 150% size / 100% coverage (Typ)	Recycle/Disposal:	Please local,
Pixel Size:	0.179 mm (H) x 0.179 mm (V)	Warranty:	*Warra marke
Surface Treatment:	Glare, Hard Coating (N/A)	Power Management:	Energy
COMPATIBILITY			
PC Resolution (max):	1920x1080		
Mac® Resolution (max):	1920x1080		
PC Operating System:	Windows 10/11 certified; macOS tested		
Mac® Resolution (min): CONNECTOR	1920x1080		
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	2 (40W power charger)		
3.5mm Audio Out:	1		
Micro HDMI 1.4 In:	1		
Power in:	USB Type C (with video & data)		
AUDIO			
Internal Speakers:	1Watts x2		
POWER			
Eco Mode (Conserve):	5W		
Eco Mode (optimized):	6W		
Consumption (typical):	7W		
Consumption (max):	15W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
CONTROLS			
Physical Controls:	Up, Down, Left/Return, Right/Confirmed, Power		
On Screen Display:	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
NPUT SIGNAL			
Frequency Horizontal:	24 ~ 83KHz		
Frequency Vertical:	50 ~ 61Hz		
/IDEO INPUT			
Digital Sync:	TMDS - micro HDMI (v1.4), Micro- Packet - Type C		
ERGONOMICS			
Till (Farmand/Back)	600 / 200		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

Tilt (Forward/Back):

-60° / 20°