Key **Features**

- 100% sRGB wide color gamut coverage
- Hardware color calibration
- Delta E < 2 color accuracy
- Pre-calibrated uniformity correction
- 21:9 aspect ratio



Product **Description**

With an immersive curved screen and stunning WQHD+ 3440 x 1440 resolution, the ViewSonic VP3481a monitor elevates your viewing experience from flat to panoramic. With Pantone validated 100% sRGB color coverage, and an amazing Delta E<2 value, this 4K monitor provides industry standard color accuracy to ensure superior results, while HDR10 compatibility delivers a wider dynamic range of vivid colors and richer contrast. Thanks to an expansive 34" frameless screen, ultra-wide 21:9 aspect ratio, and integrated speakers, this monitor is ideal for video editing, content development, and other color-critical applications. Featuring an incredible 100Hz refresh rate and AMD FreeSync™ technology, this monitor delivers smooth, tear-free playback ideal for video editors and game developers. With a sleek and modern design, the VP3481a features a future-proof USB-C port as well as DisplayPort technology, and HDMI. What's more, HDCP 2.2 content protection is standard across all ports to provide secure 4K content playback, streaming and gaming. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, and other professional applications.

Visit Us

www.viewsonic.com

DISPLAY		OPERATING CONDITIONS	
Display Size (in.):	34	Temperature:	32°F to 104°F (0°C to 40°C)
Viewable Area (in.):	34	Humidity (non-condensing):	20% to 90%
Panel Type:	VA Technology	WALL MOUNT	
Resolution:	3440 x 1440	VESA Compatible:	100 x 100 mm
Resolution Type:	WQHD+	INPUT SIGNAL	
Static Contrast Ratio:	3,000:1 (typ)	Frequency Horizontal:	15 ~ 135KHz
Dynamic Contrast Ratio:	20M:1	Frequency Vertical:	24 ~ 100Hz
Light Source:	LED	VIDEO INPUT	
Brightness:	400 cd/m² (typ)	Digital Sync:	PCI-E - DisplayPort (v1.4), TMDS - HDMI (v2.0), Micro-Packet - Type C
Colors:	16.7M	ERGONOMICS	TIBINI (V2.0), MICIO-I acket - Type C
Color Space Support:	8 bit true	Height Adjust (mm):	130
Aspect Ratio:	21:9	Swivel:	120°
Response Time (Typical GTG):	5ms	Tilt (Forward/Back):	-6° / 21°
Response Time (GTG w/OD):	5ms	WEIGHT (IMPERIAL)	0 721
Viewing Angles:	178° horizontal, 178° vertical	Net (lbs):	24.6
Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (lbs):	16.1
Curvature:	1800R	Gross (lbs):	37.9
Refresh Rate (Hz):	100	WEIGHT (METRIC)	07.3
Variable Refresh Rate		Net (kg):	11.2
Technology:	FreeSync	Net Without Stand (kg):	7.3
Blue Light Filter:	Yes	Gross (kg):	17.2
Flicker-Free:	Yes	DIMENSIONS (IMPERIAL) (W	
Color Gamut:	Adobe RGB: 89% size / 83% coverage (Typ)DCI-P3: 88% size / 88% coverage (Typ)EBU: 119% size / 100% coverage (Typ)REC709: 120% size / 100% coverage (Typ)SMPTE-C: 130% size / 100% coverage (Typ)NTSC: 85% size (Typ)RGB:	Packaging (in.):	38 x 14.6 x 20.7
		Physical (in.):	31.9 x 18.91~21.23 x 9.6
		Physical Without Stand (in.):	31.9 x 14.4 x 4.1
		DIMENSIONS (METRIC) (WXI	
	120% size / 100% coverage (Typ)	Packaging (mm):	965 x 370 x 525
Pixel Size:	0.232 mm (H) x 0.232 mm (V)	Physical (mm):	809 x 480.46~539.23 x 243
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (mm):	809 x 366 x 105
COMPATIBILITY		GENERAL	
PC Resolution (max):	3440×1440		cTUVus, FCC-B, ICES003, Energy
Mac® Resolution (max):	3440x1440 Windows 7/8/8.1/10 certified; macOS	Regulations:	Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC, UKSEPRO, UKCA, RCM, CCC, China RoHS, China Energy Label,
PC Operating System: Mac® Resolution (min):	tested 3440x1440		
CONNECTOR	377071770		CECP
USB 3.2 Type A Down Stream:	2	PACKAGE CONTENTS:	VP3481A x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
USB 3.2 Type B Up Stream:	1		
USB 3.2 Type C Up Stream;	1		
DisplayPort Alt mode :	2	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
HDMI 2.0 (with HDCP 2.2):	2		*Warranty offered may differ from
DisplayPort:	1 2 nin Saakat (IEC C14 / CEE22)	Warranty:	market to market
Power in:	3-pin Socket (IEC C14 / CEE22)	Power Management:	Energy Star standards, EPEAT
Ethernet LAN (RJ45):	1		
AUDIO	5W # 0		
Internal Speakers:	5Watts x2		
POWER	24 9 0 0		
Eco Mode (Conserve):	24.8W		
Eco Mode (optimized):	28.7W		
Consumption (typical):	33.6W		
Consumption (max):	38.6W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization: CONTROLS	Yes		
Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

On Screen Display: