



LCD DISPLAY

VX2719-PC-MHD

Key Features

- 240Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- 1500R Curved screen for immersive visuals
- AMD FreeSync™ Premium prevents screen tearing
- Full HD resolution for rich detail



Product Description

Get ready to game on the VX2719-PC-MHD 27" Full HD display. Take your experience further with the immersive 1500R curve, which puts your gameplay in focus. The ultra-responsive 240Hz display provides pro level refresh rates so you can stay ahead of the competition and enjoy ultra-smooth gaming no matter how intense the action gets. A clean design, with 3-side borderless display and sleek dimensions create a product that delivers all you need. AMD FreeSync™ Premium virtually eliminates screen tearing and stuttering for a fluid gaming experience. And the 1ms MPRT response time enables you to react in-game with complete precision. VX2719-PC-MHD is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer optimized screen performance for a variety of needs, such as gaming, editing, or watching movies. In addition, a DisplayPort and HDMI inputs offer flexible connectivity for gaming and entertainment.

Visit Us www.viewsonic.com



DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colours:	16.7M
Colour Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	1500R
Refresh Rate (Hz):	240
Variable Refresh Rate Technology:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes
Colour Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.311 mm (H) x 0.311 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0:	2
DisplayPort:	1
Power in:	External power adapter

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	26W
Eco Mode (optimized):	28W
Consumption (typical):	31W
Consumption (max):	35W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.5W
Power Supply:	External

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	75 x 75 mm
------------------	------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 31.469 ~ 291.309KHz, DisplayPort (v1.2): 31.469 ~ 219.309KHz
Frequency Vertical:	HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.2): 48 ~ 240Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2)
---------------	--

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	8.6
Net Without Stand (lbs):	7.3
Gross (lbs):	12.1

WEIGHT (METRIC)

Net (kg):	3.9
Net Without Stand (kg):	3.3
Gross (kg):	5.5

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	27 x 17.4 x 6.1
Physical (in.):	24 x 18.7 x 8.8
Physical Without Stand (in.):	24 x 14.3 x 2.9

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	687 x 443 x 156
Physical (mm):	611 x 475 x 225
Physical Without Stand (mm):	611 x 363 x 75

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, BIS
PACKAGE CONTENTS:	VX2719-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market