EB-PU1008W



The EB-PU1008W is a compact and versatile high brightness projector with optional interchangeable lenses and advanced installation features.

This highly versatile 8,500 lumens installation projector is sold as 'body only' and pairs seamlessly with Epson's existing lens family to deliver bright, true-to-life images in a wide variety of environments: from visitor attractions to lecture theatres, museums to meeting rooms. The high lumens EB-PU1008W offers WUXGA resolution with 4K enhancement, HDR and advanced installation features.

Superior image quality

The 8,500 lumens EB-PU1008W projects clear whites, vivid details, deep blacks, defined shadows and high contrast imagery.

Compact and lightweight

The compact size makes this projector more transportable and saves storage space, providing size and cost advantages to projector fleets. The unobtrusive design allows it to blend seamlessly into most environments. Also available in black.

Interchangeable lens support

The EB-PU1008W accommodates different lenses to suit a wide range of projection environments, including a zero-offset ultra-short-throw lens. Epson supplies the projector as 'body only', without a lens, which puts the power to build the right projection solution, for the right application, in the hands of the user.

Designed for installation agility

Produce large-scale, extremely bright displays, even as part of multi-projector installations where edge blending, stacking and lens flexibility is key. Epson Projector Professional Tool makes advanced installation techniques easy, such as projection mapping, while the optional external camera module (ELPEC01) uses built-in processing for PC-free geometry correction for stacking. The EB-PU1008W also features NFC for multi-projector set up, making diagnostics and installations easier using the Epson Projector Config Tool.

DATASHEET / BROCHURE

































KEY FEATURES

- Compact and lightweight
 Unobtrusive and easier to transport
- Lens support
 Supports a wide selection of Epson interchangeable lenses
- Enhanced design
 Clean, simple, and discreet design.
- Image quality 8,500 lumens, 3LCD, WUXGA resolution with 4K enhancement
- Advanced installation tools
 A range of free software tools and an optional external camera module





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.76 inch with C2 Fine

IMAGE

Color Light Output 8,500 Lumen - 5,950 Lumen (economy) In accordance with IDMS15.4

White Light Output 8,500 Lumen - 5,950 Lumen (economy) In accordance with ISO 21118:2020

Resolution WUXGA
High Definition 4K enhancement
Aspect Ratio 16:10

Contrast Ratio Over 2,500,000 : 1

Native Contrast 2,000 : 1 Light source Laser

Laser Light source 20,000 hours Durability High, 30,000 hours Durability Eco

Keystone Correction Manual vertical: \pm 45 °, Manual horizontal \pm 30 °

Colour Reproduction Upto 1.07 billion colours

OPTICAL

0.35 - 10.11:1 Throw Ratio Zoom Motorized Lens Shift varies by lens Screen Size varies by lens Projection Distance Wide)varies by lens Projection Distance Tele)varies by lens Projection Lens F Number varies by lens Projection Lens Focal Length varies by lens Projection Lens Focus Motorized Interchangeable Lens Yes Not included Standard Lens

CONNECTIVITY

Interfaces USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10

Base-T), Wireless LAN IEEE 802.11a/b/g/n (optional), VGA in, DVI in, HDBaseT, Jack plug out, HDMI (HDCP 2.3), Near Field Communication (NFC), USB content playback, Remote

ADVANCED FEATURES

Security Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock,

Wireless LAN security, Password protection

Other features 21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Auto source search,
Direct Power on/off, Edge Blending, Long light source life, OSD copy function, Point

correction, Power on button, Quick Corner, Schedule Function, Super resolution, Web Control,

Web Remote, iProjection App

Video Color Modes Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709

Projector control via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery

GENERAL

Power consumption 462 Watt - On mode power consumption (Normal)

535 Watt (Peak), 452 Watt (Eco), 0.5 Watt (Energy saving standby)

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 545 x 436 x 189 mm (Width x Depth x Height)

OTHER

Warranty 36 months Carry in

Optional warranty extension available

EB-PU1008W

WHAT'S IN THE BOX

- Remote control incl. batteries
- Power cable
- Cable cover
- Lens connector cap
- User's Manual Set
- Warranty Documents



OPTIONAL ACCESSORIES

Adapter - ELPAP11 Wireless LAN (5GHz)

V12H005A01

• Air Filter - ELPAF46

V13H134A46

• Camera Unit - ELPEC01

V12HA46010

• External Air Filter - ELPAF63 - EB-PU1000 Series

V13H134AD0

• Ceiling Mount - ELPMB68

V12H006AE0

• Portrait Adaptor - ELPMB69 - For ELPMB68

V12H006AF0

• Extension Pole - ELPMB70 - For ELPMB68

V12H006AG0

• Truss Adaptor - ELPMB71 - For ELPMB68

V12H006AH0

Stacking Frame - ELPMB76 - EB-PU1000 Series

V12H006AN0

OPTIONAL LENSES

 Lens - ELPLL08 - Long throw - EB-PU Series V12H004L08

 Lens - ELPLM08 - Mid throw 1 - EB-PU1000 Series V12H004M08

 Lens - ELPLM10 - Mid throw 3 - EB-PU Series V12H004M0A

 Lens - ELPLM11 - Mid throw 4 - EB-PU Series V12H004M0B

• Lens - ELPLM15 - Mid throw - EB-PU Series

V12H004M0F

● Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series

V12H004UA3

• Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series

V12H004U04

• Lens - ELPLW05 - Wide zoom 1 - EB-PU Series

V12H004W05

• Lens - ELPLX01WS - UST - EB-PU Series

V12H004Y0A

LOGISTICS INFORMATION

SKU	V11HA33940
EAN code	8715946697291
Country of Origin	Philippines

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie



EB-PU1008W