



T8 TUBES : BYPASS/LINE VOLTAGE : DOUBLE-ENDED

DESCRIPTION

LED T8 Replacement Lamps directly replace fluorescent T8 lamps at a fraction of the energy cost.

FEATURES

- Solid state replacement for 2', 3', or 4' T8 linear fluorescent
- Use with shunted (T8) or non-shunted (T12) lamp holders
- Frosted lens for uniform diffuse appearance
- No external ballast or driver required
- Ultra-high performance LEDs deliver 121+ lpw
- Instant-On with no warm up like fluorescents
- Integral 120~277V drivers provide easy installation
- Contains no mercury or lead; classified as non-hazardous waste
- Use with shunted (T8) or non-shunted (T12) lamp holders
- Note: Both pins on each end of lamp must be connected to line voltage. Non-shunted (T12) lamp holders require field-installed jumper wire tying both pins together; see wiring diagram.

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Commercial
- Conference rooms
- Hospitality
- Education
- Healthcare
- Retail
- Residential



	Power Consumption	9W	12W	14W	17W
PERFORMANCE	Lumens	1,150	1,400/1,450	1,700/1,800	2,100/2,200
	Efficacy (LPW)	128	117/121	121/129	124/129
	CRI	80+			
	CCT	3500K, 4000K, 5000K			
	Life (L70)	50,000 hours			
	ELECTRICAL	Power Factor	≥0.97		
THD		<20%			
Input Voltage		120V			
CONSTRUCTION	Operating Temperature	-4°F to 113°F (-20°C to 45°C)			
	Base	G13			
	Lens	Frosted			
LISTINGS	Certification(s)	DesignLights Consortium® Qualified; NSF Listed; cULus Listed; FCC			
	Material Usage	RoHS Compliant; no mercury or lead			
	Environment				