



Bore Mount Flange Facing Machine 8-42" (203 -1066mm)



SPECIFICATION Min Facing Diameter 6" (153mm) 42" (1066mm) Max Facing Diameter 7 7/8" (147mm) Min Clamp Diameter Max Clamp Diameter 32" (813mm) 4" (102mm) Tool Post travel **RPM** 30 Pneumatic 2.2Hp @ 6 Bar 67 CFM

W&Ds			
Machine Weight	88kg		194lbs
Shipping Weight	250kgs		550lbs
Shipping Dimension	Length 94cms	Width 59cm	Height 110cm s
		S	· J

KEY FEATURES

- Heavy Duty Precision construction
- High torque planetary gear drive
- 3 continuous groove in/out facing feeds to provide a gramophone finish (ASMEStandard).
- Auto Boring Feed
- Adjustable base with 8off clamping legs and
- extensions for quick & ridged set on site Hardened slide ways to maintain long term accuracy
- 360 degrees swivel tool post for groove details

DESCRIPTION

An internally mounted flange facing machine capable of producing a continuous groove gramophone finish to ASME Standard along with the capability to auto feed groove profiles

FACING FEED RATES	IN/REV	MM/REV	GROOVE / INCH
1 -In	0.039"	0.31m	81
1 -Out	0.021"	m	46
2 -In	0.018"	0.55m	55
2 -Out	0.031"	m	32
3 -In	0.023"	0.46m	42
3 -Out	0.039"	m	24
		0.79m	

INCLUDED AS STANDARD WITH MACHINE

The machine is supplied complete with the following items;

- ✓ All clamping feet, mounting № №
- ✓ Toolkit including tools and inserts
- ✓ Air filter lubricator
- ✓ Hose connection
- ✓ Storage / shipping box
- ✓ Packing list and manual

Axis Machines Pte Ltd, 1 Tuas View Place, 02-04 Westlink One, 637433, Singapore







