

90° CORNER SECTION FOR 9W/M COB RIBBON | IP20



BL-LS-COB9-90-WW



BL-LS-COB9-90-NW

| COLOUR | CODE | INGRESS PROTECTION | LUMENS | EFFICACY |
|---------------------|------------------|---------------------------|---------|----------|
| WARM WHITE 3000K | BL-LS-COB9-90-WW | IP20 General interior use | 769lm/m | 85lm/W |
| NATURAL WHITE 4000K | BL-LS-COB9-90-NW | | 875lm/m | 97lm/W |

COLOUR VARIANCE +/- 200K
ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%
SOLD BY THE METRE

| | | | | | |
|-----------------|-------------------------|-------------|--------------|----------|---|
| LED WATTS | 9W/m | CRI | ≥90 | MOUNTING | 3M adhesive backing A Bright Light approved aluminium profile is required for thermal management |
| INPUT VOLTS | 24V DC constant voltage | BEAM ANGLE | 180° | POLARITY | Polarity alternates sides on corner |
| OPERATING TEMP. | -25°C ~ +50°C | SOURCE LIFE | 50,000 hours | CONTROL | Dimmable by PWM signal |
| | | WARRANTY | 3 years | | |

