

4 × 5A DMX WIRELESS DECODER RECEIVER



CODE
BL-PC-LT8745A

FUNCTION
<ul style="list-style-type: none"> - Frequency of 2.4GHz ISM 64 channels, up to 300 metres - DMX control for single colour, Tuneable white, RGB, and RGBW LED ribbon strip or other constant voltage luminaires - One receiver is required to be used with each transceiver (BL-DMX-104) - Ideal for retro fit applications where cable installation is a challenge - Digital addressing

OUTPUT CURRENT	MAX. LOADING	VOLTS
4 × 5A channels (20A)	100W	5V DC
	240W	12V DC
	480W	24V DC

DIMENSIONS	W44 × L175 × H30mm
HOUSING	PVC casing
MOUNTING	2 × mounting tabs
WARRANTY	5 years

COMPLIANCE	
------------	---

OPERATING TEMP.	-30°C ~ +55°C
INGRESS PROTECTION	Indoor use only
CONNECTION METHOD	Concealed screw terminals
CONTROL	Requires DMX 512 signal from transceiver (BL-DMX-104)
FREQUENCY	2.4GHz <i>Up to 300 metres. Steel, concrete, or environmental conditions will inhibit transmission.</i>
MAX. DISTANCE FROM POWER SUPPLY	Recommended under 10 metres <i>For specific projects contact Bright Light</i>