BRIGHTLIGHT

PRODUCT SPECIFICATIONS



BASELINE 01 MINI





FEATURES


- W20 × H10mm
- Rolled opal diffuser (continuous up to 50m)
- Anodised aluminium, black or white powder-coat finishes
- Self-countersinking screw design
- Surface or recess mount
- Provides thermal management for LED ribbon up to a maximum of Pro 12 or equivalent
- For best visual performance COB LED is recommended to ensure a dot-free result

FINISH	DIFFUSER	CODE	ACCESSORY	CODE
ANODISED	ROLLED OPAL	BL-LP-B01MV2ARO-XX	ALUMINIUM END CAP W20 × H10 × D2MM	BL-LP-B01MV2X-EC
BLACK		BL-LP-B01MV2BRO-XX	JOINER STRAIGHT	BL-LP-J101S
WHITE		BL-LP-B01MV2WRO-XX	JOINER 90° CORNER	BL-LP-J102C
XX = (2M) 2 METRE or (4M) 4 METRE LENGTHS			JOINER 120° CORNER	BL-LP-J121C

JOINER VERTICAL TO HORIZONTAL BL-LP-J103VH

END CAPS SOLD INDIVIDUALLY X = (A) ANODISED, (B) BLACK, OR (W) WHITE

DIMENSIONS



INSTALLATION

