BRIGHTLIGHT

PRODUCT SPECIFICATIONS



BASELINE 06






FEATURES

- W18.5mm × H31mm
- Curved frosted acrylic diffuser
- Anodised aluminium, black, or white powder-coat
- Suspend or surface mount
- Provides thermal management for LED ribbon up to a maximum of Pro 30 or equivalent
- For best visual performance LED ribbon up to a maximum of Pro 12 or equivalent is recommended for glare management.


DIFFUSER	FINISH	CODE	
OPAL	ANODISED	BL-LP-B06AO-XX	
	BLACK	BL-LP-B06BO-XX	
	WHITE	BL-LP-B06WO-XX	
XX = (2M) 2 METRE or (4M) 4 METRE LENGTHS			

XX = (2M) 2 METRE or (4M) 4 METRE LENGTHS

DIMENSIONS



INSTALLATION



ACCESSORY	CODE
ALUMINIUM END CAP W18.5 × H31 × D2MM	BL-LP-B06X-EC
JOINER STRAIGHT	BL-LP-J101S
JOINER 90° CORNER	BL-LP-J102C
JOINER 120° CORNER	BL-LP-J121C
CABLE BASE SURFACE MOUNT	BL-LP-S104X
CABLE BASE RECESSED	BL-LP-S105X
CABLE BASE MINI 38MM	BL-LP-S112X
SUSPENSION WIRE WITH BASE	BL-LP-S106X

END CAPS SOLD INDIVIDUALLY X = (A) ANODISED, (B) BLACK, OR (W) WHITE







BL-LP-S104X

X BL-LP-S105X

BL-LP-S112X

0800 952 000 | www.brightlight.co.nz | BRIGHTLIGHT

Actual product characteristics may vary. Bright Light reserves the right to improve, modify or update the product designs without prior notice.