

## ENCAPSULATED | SHEER




COLOUR	CODE	LUMENS
3000K WARM WHITE	BL-LS-4325-30	≥530lm/m
4000K NATURAL WHITE	BL-LS-4325-40	≥580lm/m


COLOUR VARIANCE +/- 200K  
ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%  
SOLD BY THE METRE

LED WATTS	7.2W/m	CRI	≥80	MINIMUM BEND RADIUS	25mm
INPUT VOLTS	24V DC constant voltage	BEAM ANGLE	180°	BEND DIRECTION	Vertical bending
OPERATING TEMP.	-20°C ~ +55°C	SOURCE LIFE	50,000 hours	CUTTING LENGTH	50mm
MAX. RUN PER POWER FEED	10m using one feed 20m using two feeds	WARRANTY	3 years	DIMENSIONS	W12 × H12mm (W14mm for connectors)
				INGRESS PROTECTION	Protection established by use of IP66 connections
				HOUSING	UV resistant Silicone
				CONTROL	Dimmable by PWM signal


### DIMENSIONS



### MINIMUM BEND RADIUS



### BEND DIRECTION



Connectors & end caps require sealing internally with silicone for IP66 protection.


ACCESSORY	CODE
SIDE / BOTTOM FEED CONNECTOR IP66	BL-LS-4331
END CAP IP66	BL-LS-4332
MOUNTING CLIP 30MM	BL-LS-4330
POWER FEED CABLE (1000MM)	BL-LS-4310



SIDE / BOTTOM FEED CONNECTOR



END CAP



MOUNTING CLIP 30MM