



## LED RING PENDANT



CODE	LED WATTS	LUMENS	FINISH	DIMENSIONS	WEIGHT
BL-G-RP600B-XX	40W	3400lm	Black	D600 × W32 × H38mm	3.4kg
BL-G-RP600W-XX			White		
BL-G-RP900B-XX	50W	4250lm	Black	D900 × W32 × H38mm	4.6kg
BL-G-RP900W-XX			White		
BL-G-RP1200B-XX	80W	6800lm	Black	D1200 × W32 × H38mm	5.9kg
BL-G-RP1200W-XX			White		
BL-G-RP1500B-XX	100W	8500lm	Black	D1500 × W32 × H38mm	7kg
BL-G-RP1500W-XX			White		

XX = WW (WARM WHITE), NW (NATURAL WHITE) OR CW (COOL WHITE)

VOLTS	220–240V AC 50/60Hz input	BEAM ANGLE	120°	MATERIAL	Aluminium 6063 body & PC lens diffuser
OPERATING TEMP. (ENVIRONMENT)	-20°C ~ +40°C	EFFICACY	85lm/W	FINISH	Matt black or matt white
		COLOUR	Warm White 3000K Natural White 4000K Cool White 5000K	INGRESS PROTECTION	Indoor use only
		CRI	≥80	MOUNTING	Ø250mm Central Mounting bracket Suspended with 1.5m power cable and safety cable
		POWER FACTOR	≥0.90	CONTROL	Non-dimmable
		SOURCE LIFE	50,000 hours	LEAD TIME	6-8 weeks
		BIN	3-step MacAdam ellipse		
		WARRANTY	3 years		
		COMPLIANCE			

