

24V POWER SUPPLIES | IP20



CODE	OUTPUT WATTS	OUTPUT AMPS	POWER FACTOR	AC INRUSH CURRENT	DIMENSIONS
BL-PS-15-24	15W	0.62A	0.5	50A peak @ 230V	W45 × H19 × L123mm
BL-PS-30-24	30W	1.25A	0.9	60A peak @ 230V	W50 × H17 × L156mm
BL-PS-50-24	50W	2.08A	0.9	75A peak @ 230V	W58 × H18 × L160mm
BL-PS-75-24	75W	3.13A	0.95	75A peak @ 230V	W44.5 × H28.2 × L170mm
BL-PS-100-24	100W	4.17A	0.9	75A peak @ 230V	W65.5 × H31.2 × L180mm
BL-PS-150-24	150W	6.25A	0.9	75A peak @ 230V	W62.5 × H30.6 × L179.4mm
BL-PS-200-24	200W	8.33A	0.9	75A peak @ 230V	W67.1 × H31.2 × L195mm

INPUT VOLTS	200–240V AC	WARRANTY	3 years	INGRESS PROTECTION	Indoor use only
OPERATING TEMP.	-20°C ~ +45°C	COMPLIANCE		ELECTRICAL PROTECTION	Overload, short circuit, overheat, and automatic re-start
DISTANCE FROM INSTALLATION (Secondary Output)	Recommended under 10 metres			CONNECTION METHOD	Concealed screw terminals, 1.5mm max
				CONTROL	Dimmable on the secondary output only by PWM