


LIGHTING 6-CIRCUIT TRACK SYSTEM

Installation Guide

PE





RECESSED

250V AC · 16A · 50/60Hz · Class I · IP20 Compatible with 1-10V, DALI

CE

	BL-CS-TC34W BL-CS-TC34B BL-CS-TC34FW BL-CS-TC34FB	Surface Mounted White Track Surface Mounted Black Track Recessed White Track Recessed Black Track	612 -	BL-CS-CCU3AW BL-CS-CCU3BW BL-CS-CCU3AB BL-CS-CCU3BB	White Connection Unit A White Connection Unit B Black Connection Unit A Black Connection Unit B
	BL-CS-CJU3	Joint Connector Black or white cover		BL-CS-CMCU3W BL-CS-CMCU3B	White Middle Connector Black Middle Connector
1	BL-CS-CLC3W BL-CS-CLC3B	90° White Corner Connector 90° Black Corner Connector	andrey D	BL-CS-A100W BL-CS-A100B	White Pendant Adaptor Black Pendant Adaptor
	BL-CS-CXA3W BL-CS-CXA3B	White X-Angle Connector Black X-Angle Connector	a b	BL-CS-CTA3AW BL-CS-CTA3BW BL-CS-CTA3CW BL-CS-CTA3DW BL-CS-CTA3AB	White T-Angle Connector A White T-Angle Connector B White T-Angle Connector C White T-Angle Connector D Black T-Angle Connector A
enterer	BL-CS-CEC3W BL-CS-CEC3B	White End Cap Black End Cap	-	BL-CS-CTA3BB BL-CS-CTA3CB BL-CS-CTA3DB	Black T-Angle Connector B Black T-Angle Connector C Black T-Angle Connector D
	BL-CS-CS3W BL-CS-CS3B	White Blank Cover Black Blank Cover		BL-CS-CCP3W BL-CS-CCP3B	White Recessed Cover Plate Black Recessed Cover Plate

NOTE:

Only components belonging to this track system should be used, and the components must be installed according to these installation instructions.

Bright Light is not responsible for the safety and function of this system if components not belonging to this system are used, or if the installation instructions are not followed.


It is the user's responsibility to ensure the electrical, mechanical, and thermal compatibility between the system and the fixtures attached to it.


The user must test all connections and electrical lines before attaching luminaires or other features to the system.




MOUNTINGACCESSORIES


	1		
 BL-CS-CB3WWhite Ceiling BracketBL-CS-CB3BBlack Ceiling Bracket		BL-CS-WBW BL-CS-WBB	White Wall Bracket Black Wall Bracket
BL-CS-WS40HAdjustable Suspension Kit With Hook (4m) SilverBL-CS-WS40HBAdjustable Suspension Kit With Hook (4m) Black		BL-CS-WS40 BL-CS-WS40B	Silver Wire Suspension Black Wire Suspension
BL-CS-PBWWhite Pendant BracketBL-CS-PBBBlack Pendant Bracket		BL-CS-QCBW BL-CS-QCBB	White Quick Ceiling Bracket Black Quick Ceiling Bracket
BL-CS-PCW White Pendant Coupler BL-CS-PCB Black Pendant Coupler		BL-CS-CB3WT BL-CS-CB3BT	White T-Bar Ceiling Bracket Black T-Bar Ceiling Bracket
BL-CS-GT-6 Silver Threaded Rod BL-CS-SS-6W White Sleeve for Threaded Rod			
BL-CS-CBCW White Ceiling Bracket with Cup BL-CS-CBCB Black Ceiling Bracket with Cup			
BL-CS-PBAWWhite Adjustable Pendant BracketBL-CS-PBABBlack Adjustable Pendant Bracket	-		
]		






0800 952 000 | www.brightlight.co.nz | BRIGHTLIGHT










0800 952 000 | www.brightlight.co.nz | BRIGHTLIGHT

X-ANGLE CONNECTOR









0800 952 000 | www.brightlight.co.nz | BRIGHTLIGHT










PHYSICAL LOADING

For all mounting types (surface, recessed and suspended) physical loading should be spread out across length as per diagrams below.





0800 952 000 | www.brightlight.co.nz | BRIGHTLIGHT



THREADED ROD SUSPENSION INSTALLATION