


METRO 2.0 LED TRACK SPOT LIGHTS



SYSTEM WATTS	CODE	POWER FACTOR	BEAM ANGLE	COLOUR	LUMENS	EFFICACY
28W	BL-G-7200X-WW-D	≥0.925	15°	Warm White 3000K	2350lm	84lm/W
	BL-G-7200X-NW-D			Natural White 4000K	2530lm	90lm/W
	BL-G-7201X-WW-D		25°	Warm White 3000K	2470lm	88lm/W
	BL-G-7201X-NW-D			Natural White 4000K	2660lm	95lm/W
	BL-G-7202X-WW-D		45°	Warm White 3000K	2540lm	91lm/W
	BL-G-7202X-NW-D			Natural White 4000K	2730lm	97lm/W
	BL-G-7203X-WW-D		60°	Warm White 3000K	2370lm	84lm/W
	BL-G-7203X-NW-D			Natural White 4000K	2560lm	91lm/W

IES FILES AVAILABLE

VOLTS	220–240V AC 50/60Hz input	CRI	93	DIMENSIONS	<i>Light</i> Ø91 × H130mm
OPERATING TEMP.	-20°C ~ +35°C	SDCM	3-Step MacAdam		<i>With Base</i> H196mm
		SOURCE LIFE	50,000 hours	ADJUSTMENT	90° tilt 350° rotation
		LIFETIME	L80, B20	HOUSING	Die-cast aluminium
		WARRANTY	5 years	FINISH	Black or White
		COMPLIANCE		WEIGHT	0.35kg
				INGRESS PROTECTION	Indoor use only
				CONNECTION METHOD	3-phase DALI track connector
				CONTROL	DALI