




## NEON MICRO CLASSIC | WHITE | PVC



COLOUR	CODE	LUMENS	
WARM WHITE 3000K +/- 175K	BL-LS-4550-30	≥160lm/m	
NATURAL WHITE 4000K +/- 275K	BL-LS-4550-40	≥160lm/m	

ELECTRICAL & OPTICAL DATA VARIANCE +/- 10% SOLD BY THE METRE IES FILES AVAILABLE

With the introduction of our indent range of Silicone encapsulated Neon LED ribbon, our local, end of line PVC stock is available with 3 year warranty using local connectors.

Neon MIcro Classic is a perfect where a smaller profile is required W16.5 × H26mm (W11.5mm at the base).

Stock quantities vary - Talk to our team.
For more options consider our indent silicone
Neon range - lead times apply.

### APPLICATIONS

- A perfect replacement for traditional glass neon tube where a smaller profile is required
- Signage & cove lighting
- Architectural features
- Exterior or interior installations


LIDEC
UILLO

 Suitable for use around salt or chlorinated water

	LED WATTS	4.5W/m
	INPUT VOLTS	24V DC constant voltage
	OPERATING TEMP.	-20°C ~ +45°C
	MAX. RUN PER POWER FEED	15m using one feed 30m using two feeds (01 & 02 connectors)
	CRI	≥80
	CRI BEAM ANGLE	≥80 180°

MINIMUM BEND RADIUS	60mm
BEND DIRECTION	Horizontal bending
DIMENSIONS	W16.5 × H26mm (W11.5mm at the base)
INGRESS	Up to IP67
PROTECTION	Protection established by use of connection type
	SEE PAGE 2.
CUTTING LENGTH	83.3mm
HOUSING	UV & flame resistant white PVC
MOUNTING	Profile / clips available SEE PAGE 3.
CONTROL	Dimmable by PWM signal









### NEON MICRO CLASSIC | WHITE | PVC | CONNECTIONS

Neon products are IP rated based on the fitted connections (power feed / end caps).

Can be fitted on-site or pre-fitted by Bright Light.

#### CLASP CONNECTIONS | IP65



TOP END FEED CONNECTOR SUPPLIED AS 1M CABLE INSTALLATION WITH DOUBLE POWER FEED: FEED 01 + FEED 02

CONNECTOR TOLERANCE +/-0.5MM






TOP END FEED


01 02

END CAP

WHITE / SINGLE COLOUR BL-LS-4556 BL-LS-4557 BL-LS-4551



TOP END FEED



SNAP CONNECTIONS | IP67



TOP END FEED CONNECTOR SUPPLIED AS 1M CABLE INSTALLATION WITH DOUBLE POWER FEED: FEED 01 + FEED 02

MUST BE FITTED CORRECTLY FOR IP RATING



TOP END FEED

02



02





END CAP


300MM FLEXIBLE CONNECTOR

**WHITE** BL-LS-4558 BL-LS-4559 BL-LS-4561 BL-LS-4562 BL-LS-4560

01








FLEXIBLE CONNECTOR



# NEON MICRO CLASSIC | MOUNTING ACCESSORIES



CODE	ACCESSORY	L1	L2	HOLE DIMENSIONS	HOLE NUMBER
BL-LS-4552	SELF-LOCKING ALUMINIUM PROFILE 2M	100mm	200mm	Ø3.5mm	10
BL-LS-4553	SELF-LOCKING ALUMINIUM MOUNTING CLIP 50MM	25mm	-	Ø3.5mm	1
BL-LS-4554	PLASTIC PROFILE 2M	100mm	200mm	Ø3.5mm	10
BL-LS-4555	PLASTIC PROFILE 1M	100mm	200mm	Ø3.5mm	5
BL-LS-4028	CURVE STAINLESS STEEL PROFILE 890MM MULTIPLE FIXING LOCATIONS	-	-	-	-

