


EX-STOCK  
PRODUCT

## NEON MICRO EDGE | WHITE | PVC



COLOUR	CODE	LUMENS
WARM WHITE 3000K +/- 175K	BL-LS-4050-30	≥120lm/m
NATURAL WHITE 4000K +/- 275K	BL-LS-4050-40	≥120lm/m
COOL WHITE 5000K +/- 300K	BL-LS-4050-50	≥120lm/m

ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%  
SOLD BY THE METRE  
IES FILES AVAILABLE

With the introduction of our indent range of Silicone encapsulated Neon LED ribbon, our local, end of line PVC stock is available with 3 year warranty using local connectors.

Neon Micro Edge is a sleek W9 × H18mm model perfect for cove lighting, handrails, or architectural features in exterior and interior applications.

Stock quantities vary - Talk to our team.  
For more options consider our indent silicone Neon range - lead times apply.




### APPLICATIONS

- Ideal where a slimmer profile is required
- Handrails or toekicks
- Architectural features
- Exterior or interior installations

### FEATURES

- Suitable for use around salt or chlorinated water

LED WATTS	4.5W/m	MINIMUM BEND RADIUS	45mm
INPUT VOLTS	24V DC constant voltage	BEND DIRECTION	Horizontal bending
OPERATING TEMP.	-20°C ~ +45°C	DIMENSIONS	W9 × H18mm
MAX. RUN PER POWER FEED	15m using one feed 30m using two feeds (01 & 02 connectors)	INGRESS PROTECTION	Up to IP67 Protection established by use of connection type SEE PAGE 2.
CRI	3000/4000K ≥80 5700K ≥70	CUTTING LENGTH	83.3mm
BEAM ANGLE	160°	HOUSING	UV & flame resistant white PVC
SOURCE LIFE	50,000 hours	MOUNTING	Profile / clips available SEE PAGE 3.
WARRANTY	3 years	CONTROL	Dimmable by PWM signal



## NEON MICRO EDGE | WHITE | PVC | CONNECTIONS


Neon products are IP rated based on the fitted connections (power feed / end caps).

Can be fitted on-site or pre-fitted by Bright Light.

### CLASP CONNECTIONS | IP65



TOP END FEED CONNECTOR SUPPLIED AS 1M CABLE  
 INSTALLATION WITH DOUBLE POWER FEED:  
 FEED 01 + FEED 02  
 CONNECTOR TOLERANCE +/-0.5MM



TOP END FEED  
01 02


END CAP

WHITE


BL-LS-4056

BL-LS-4057

BL-LS-4051



TOP END FEED




END CAP

### SNAP CONNECTIONS | IP67



TOP END FEED CONNECTOR SUPPLIED AS 1M CABLE  
 INSTALLATION WITH DOUBLE POWER FEED:  
 FEED 01 + FEED 02  
 MUST BE FITTED CORRECTLY FOR IP RATING



TOP END FEED

END CAP

300MM FLEXIBLE  
CONNECTOR

01

02

01

02

WHITE

BL-LS-4058

BL-LS-4059

BL-LS-4061




BL-LS-4062

BL-LS-4060


TOP END FEED

END CAP





FLEXIBLE CONNECTOR




## NEON MICRO EDGE | MOUNTING ACCESSORIES



CODE	ACCESSORY	L1	L2	HOLE DIMENSIONS	HOLE NUMBER
BL-LS-4052	SELF-LOCKING ALUMINIUM PROFILE 2M	100mm	200mm	Ø3.5mm	10
BL-LS-4053	SELF-LOCKING ALUMINIUM MOUNTING CLIP 50MM	25mm	-	Ø3.5mm	1
BL-LS-4054	PLASTIC PROFILE 2M	100mm	200mm	Ø3.5mm	10
BL-LS-4055	PLASTIC PROFILE 1M	100mm	200mm	Ø3.5mm	5



**SELF-LOCKING ALUMINIUM PROFILE / MOUNTING CLIP**



**PLASTIC PROFILE**