


S50 MODULE



| COLOUR | CODE | LENS | BEAM ANGLE | LUMENS |
|------------------------|---------------|---------|------------|--------|
| WARM WHITE 2700K | BL-DL-106-27 | Clear | 60° | 900lm |
| WARM WHITE 3000K | BL-DL-106-WW | Clear | 60° | 950lm |
| | BL-DL-106F-WW | Frosted | Wide | 850lm |
| NATURAL WHITE 4000K | BL-DL-106-NW | Clear | 60° | 1000lm |

MOUNTING TRIM SOLD SEPARATELY
50W HALOGEN EQUIVALENT

| | |
|-----------------|------------------------------|
| LED WATTS | 9W |
| SYSTEM WATTS | 11W |
| VOLTS | 220-240V AC 50/60Hz input |
| OPERATING TEMP. | -35°C ~ +70°C |

| | |
|-------------|---|
| CRI | 90 |
| LED BRAND | Single COB Citizen LED with reflector |
| SOURCE LIFE | 50,000 hours |
| WARRANTY | 3 years |
| COMPLIANCE |  |

| | |
|-----------------------|---|
| DIMENSIONS | <i>Module</i> Ø55 × H70mm <i>Dimmable Driver</i> W46 × H30 × L110mm |
| HOUSING | Pressed stainless steel heatsink |
| MOUNTING | For use with Bright Light mounting trims |
| INGRESS PROTECTION | Indoor use only |
| CONNECTION METHOD | External driver with concealed screw terminals |
| CONTROL | Dimmable <i>Compatible with a range of trailing edge or universal dimmers; contact Bright Light for more information</i> |



CONEDIAGRAM

3000K

