RETREAT 1.05

Technical Specifications

Get creative with floor plans using RETREAT 1.05. Designed for both flexibility and floorspace practicality, RETREAT 1.05 has a unique aesthetic that can be used alone or with other products from the RETREAT range. With one flat side and one tapered, RETREAT 1.05 can be placed against a wall or corner, or can be incorporated into a suite of Square Bear products including multi-sized RETREAT pods, mobile storage, planters, and whiteboards.

VENTILATION

Low noise, sensor-controlled ventilation system with constant air exchange via top and base outlets with internal fan systems.

ENVIRONMENTAL DATA

60% recycled content to PET. Sustainably sourced timber FSC timber available on request.

SERVICES 畐

Seamless mechanical services integration with allowances for a sprinkler and smoke detector.

INSTALLATION

VC LIGHT

RETREAT 1.05 requires 2 men for 2-3 hours.

Dimmable touch activated

PERFORMANCE

Acoustic materials used for internal and external surfaces provide ambient noise reduction and minimise noise reverberation from the surrounding office.

ACCESS

(Ę RETREAT sits flush on the floor with a rubber seal for acoustic protection, there is no step or floor base to incumber entry.

PLUG AND PLAY

S Quick connection to mains power using standard sockets


WARRANTY

7 year structural warranty.





PRODUCT DATA





Product dimensions

External dimensions Internal dimensions People

1040/1200W x 1120D x 2178mmH 870/1035W x 990D x 2092mmH 1

Ventilation

Input

AUS

QTY of fans 4 total; 2 draw in through side, 2 draw out through ceiling 117.2CFM Air flow rate 24V DC User motion detected to 30sec / 3min / 10min

Power

Output

Mains supply

Cord from booth

10 amps 3 metres 2 gang; 1x Power, 1x USB A, 1x USB C

Lighting

Input 24V 85lm/W Lumen output LED options Natural white User motion detected to 30sec / 3min / 10min

Socket options



Motion sensor

Passive infrared sensor Running time options 30sec / 3min / 10min

VC light

Natural white Touch activated dimmable

PET Composition Sustainability VOC Emission	100% PET, 60-68% recycled Greentag certified. Greenrate level: A <0.004mg/m²/hr
Structure Faced plywood Internal External	64mm hoop pine plywood Acoustic wall paneling Acoustic wall covering
Door Door dimensions Door weight Disabled access Door hardware Drop seal	840/998W x 2068H x 8mm frameless toughened glass 25kg No wheelchair access - disability accessible Stainless steel or matte black Engaged when door is closed
Floor Levelling Floor	Adjustable glides No floor - sealed perimeter
Install Time People required	2-3 hours 2
Fire safety Fire alarm Smoke detection Sprinkler compatible	Provision provided on request Provision provided on request Provision provided on request
Cleaning PET / Upholstery Timber	Refer to product care and maintainence guide Refer to product care and maintainence guide



sales@square-bear.com TECHNICAL SPECIFICATIONS | www.square-bear.com

OPTIONS & FINISHES

RETREAT 1.05 back options



Glass back

PET back

0

RETREAT 1.05 table options



Fixed table Dimensions Height from floor Worktop finish Edge finish

880x320x32mm Dimensions 1050mmH Worktop finish White or black worktop Edge finish Natural or black stain Shelf finish



880x320x18mm Height from floor 1050mmH White or black worktop White or black Natural or black stain edge

Timber finishes






Natural

Blazer Silcoates Blazer Surrey Blazer St Andrews

Interior / exterior finishes

Black Stain



124 167 551

*Contact Square-Bear Acoustics for custom colour options.



SQUARE BEAR

© Copyright 2021 All Rights Reserved

HEAD OFFICE

Unit 6/80 Jedda Road, Prestons New South Wales 2170, Australia P: +61 (0)2 9189 1444 sales@square-bear.com

SYDNEY SHOWROOM

Level 3/140 William Street, Woolloomooloo New South Wales 2011, Australia

www.square-bear.com



RETREAT 1.05 | sales@square-bear.com TECHNICAL SPECIFICATIONS | www.square-bear.com

FREE YOUR MIND