

Expert Grade Metallic Epoxy System - Medium viscosity

EPOXYSTARZ – Part B

Revision: 11-28-23

SAFETY DATA SHEET

Section 1. Identification	
Product identifier	Epoxystarz Medium Viscosity – Part B
Other means of identification	Epoxystarz Medium Viscosity B
Recommended use and restrictions on use	Floor coating
Supplier informations	2271 Cornell Ave, Montgomery, IL 60538, United States info@specialityproductsdevelopmentgroup.com
Emergency telephone number/restriction on use	Canada – CANUTEC 24-hour number 613-996- 6666
Section 2. Hazard identification	
Classification of hazardous product (name of the category or subcategory of the haza	ard class)
Skin corrosion (Category 1) Serious eye damage (Category 1) Skin sensitization (Category 1) Specific target organ toxicity – Single exposure (Category 3) Reproductive toxicity (Category 1) Hazardous to the aquatic environment – Acute & Chronic (Category 1) Information elements (symbols, signal words, hazard statements and precautionary s	statements of the category/subcategory)
DangerH302 Harmful if swallowed.H314 Causes severe skin burns and eye damage.H317 May cause an allergic skin reaction.H335 May cause respiratory irritation.H360 May damage fertility or the unborn child.H362 May cause harm to breast-fed children.H400 Very toxic to aquatic lifeH410 Very toxic to aquatic life with long lasting effects.P201 Obtain special instructions before use. P202 Do not handle until all safety precedusts or mists. P263 Avoid contact during pregnancy and while nursing. P264 Wash for smoke when using this product. P271 Use only outdoors or in a well-ventilated arrow of the workplace. P273 Avoid release to the environment. P280 Wear protective gloveP330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P312 Call a docto off immediately all contaminated clothing. Rinse skin with water. P363 Wash contam occurs: Get medical attention. P305 + P351 + P338 IF IN EYES: Rinse cautiously with wP308 + P313 IF exposed or concerned: Get medical attention. P391 Collect spillage. Pclosed. P405 Store locked up. P501 Dispose of contents/container into safe containerOther hazards known	hands/nails/face thoroughly after handling. P270 Do not eat, drink ea. P272 Contaminated work clothing should not be allowed out es/ protective clothing/ eye protection/ face protection. P301 + r if you feel unwell. P303 + P361 + P353 IF ON SKIN (or hair): Take inated clothing before reuse. P332 + P313 IF SKIN irritation or rash vater for several minutes. Remove contact lenses, if present and d keep comfortable for breathing. P310 Immediately call a doctor. 403 + P233 Store in a well-ventilated place. Keep container tightly

Revision: 11-28-23



EPOXYSTARZ - Part B Expert Grade Metallic Epoxy System - Medium viscosity

Chemical name (common name/synonyms)	CAS number or other	Concentration (%)	
Epoxy adduct	-	10-30	
Benzyl alcohol	100-51-6	< 10	
Isophorone diamine	0002855-13-2	10-30	
Nonylphenol	84852-15-3	10-30	
Polyoxypropylene diamine	9046-10-0	30-60	
* Statement - This safety data sheet provides c volume) considered trade secret(s).	oncentration range(s) instead of the act	ual concentration(s) by weight (except for gases/propellants by	
Section 4. First-aid measures			
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.		
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.		
Skin contact	Causes severe skin burns and eye damage. IF ON SKIN: wash with plenty of water (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.		
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.		
Indication of immediate medical attention/ special treatment	In all cases, call a doctor. Also consider the other instructions of present document section.		
Section 5. Fire-fighting measures			
Specific hazards of the hazardous product (haza	rdous combustion products)		
Carbon oxides and other irritant/toxic gases ar	id fumes.		
Suitable and unsuitable extinguishing media			
In case of fire: Use carbon dioxide, chemical po	wder agent and appropriate foam to ex	tinguish surrounding products.	
Special protective equipment and precautions f	or fire-fighters		
		a without proper protection. Firefighters should wear proper ld personnel to protect from venting, rupturing	
Move containers from fire area if it can be done	without risk. Water spray may be usefu	Il in cooling equipment and cans exposed to heat and flame.	
Section 6. Accidental release measures			
Personal precautions, protective equipment and	l emergency procedures		
Restrict access to area until completion of clea should wear the appropriate protective equipm		trained personnel only. All persons dealing with clean-up	
Methods and materials for containment and clea	aning up		

Notify the appropriate authorities as required.



EPOXYSTARZ – Part B

Expert Grade Metallic Epoxy System - Medium viscosity

Section 7. Handling and storage

Precautions for safe handling

Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Section 8. Exposure controls/Personal protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: Dust - PEL-TWA 15 mg/m3 (total dust) & 5 mg/m3 (respirable fraction);

Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

Section 9. Physical and chemical properties

Appearance, physical state/colour	Liquid, clear	Vapour pressure	Not available
Odour	Characteristic	Vapour density	Not available
Odour threshold	Not available	Relative density	0.955
рН	Not available	Solubility	Not available
Melting/freezing point	Not available	Partition coefficient - n-octanol/ water	Not available
Initial boiling point/range	Not available	Auto-ignition temperature	Not available
Flash point	> 93°C	Decomposition temperature	Heavier than air
Evaporation rate	Not available	Viscosity	Not available
Flammability (solids and gases)	Not available	VOC	Not available
Upper and lower flammability/ explosive limits	Not available	Other	None know
Section 10. Stability and reactivity			
Reactivity		Does not react under the recommended storage and handling conditions prescribed.	
Chemical stability		Material is stable at standard temperature and pressure.	
Conditions to avoid		None known	
Hazardous reactions/polymerization		None known	
Incompatible materials		Oxidizing materials; Acids; etc.	

None known

Hazardous decomposition products



EPOXYSTARZ - Part B

Expert Grade Metallic Epoxy System - Medium viscosity

Section 11. Toxicological information		
Section 11. Toxicological information		
Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)	Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May damage fertility or the unborn child. May cause harm to breast-fed children.	
Symptoms related to the physical, chemical and toxicological characteristics	Skin burn, redness, stinging, pain; Eye burn, redness, tearing; Digestive tract burn; Respiratory tract burn, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.	
yed and immediate effects (chronic effects from short-term and long- exposure) Skin Sensitization – Possible; Respiratory Sensitization – available; Germ Cell Mutagenicity – No data available; Ca No ingredient listed by IARC, ACGIH, NTP or OSHA; Reprod – Possible; Specific Target Organ Toxicity — Single Exposu Specific Target Organ Toxicity — Repeated Exposure – No Aspiration Hazard – No data available; Health Hazards No Classified – No data available.		
Numerical measures of toxicity (ATE; LD50 & LC50)	CAS 9046-10-0 LD50, Oral- Rat - 2885.3 mg/kg; LC50, Inhalation - Rat - 8h > 0.74 mg/l; LD50, Dermal- Rabbit - 2980 mg/kg; CAS 2855-13-2 LD50, Oral - Rat 1030 mg/kg; CAS 84852-15-3 LD50 Oral - Rat - 1246 mg/kg & LD50 Dermal - Rabbit - 2040 mg/kg; CAS 100-51-6 LD50, Oral - Rat 1360 mg/kg; ATE not available in this document.	
Germ cell mutagenicity	Not available	
Reproductive toxicity	Not available	
Specific target organ toxicity (single exposure)	Not available	
Specific target organ toxicity (repeated exposure)	Not available	
Aspiration hazard	Not available	
Section 12. Ecological information		
Ecotoxicity (aquatic and terrestrial information)	Not available	
Persistence and degradability	Not available	
Bioaccumulative potential	Not available	
Mobility in soil	Not available	
Other adverse effects	Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.	
Section 13. Disposal considerations		
Information on safe handling for disposal/methods of disposal/ contaminated packaging	Dispose of contents/container into safe container in accordance with local, regional or national regulations.	
Section 14. Transport information		
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations	UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Isophorone diamine; Nonylphenol); CLASS 8; PG III	
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)	UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Isophorone diamine; Nonylphenol); CLASS 8; PG III	
UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)	UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Isophorone diamine; Nonylphenol); CLASS 8; PG III	
Special precautions (transport/conveyance)	May also be shipped as a LIMITED QUANTITY in accordance with TDG.	
Environmental hazards (IMDG or other)	MARINE POLLUTANT	
Bulk transport (usually more than 450 L in capacity)	Possible	



EPOXYSTARZ - Part B

Expert Grade Metallic Epoxy System - Medium viscosity

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.