

Fast Set

screen blackout coating

DESCRIPTION

Fast Set is a heavy duty, water soluble blackout coating formulated to fill in open areas of the emulsion on screens. This medium viscosity product is fast drying and spreads easily. The blue formula creates a contrast which provides easy spotting out and fills in gaps between the emulsion edge and the frame. Works great on pinholes. Designed for use with plastisol, conventional, UV and water based inks.

ADVANTAGES

- Fast drying
- One coat coverage
- Biodegradable and drain safe
- Contains no VOC's
- Easy to use
- Great on all mesh counts
- Water soluble / cleans up with water
- No odor

DIRECTIONS

- 1) Make sure that the screen is dry and free of dust or other contaminates. Pour Fast Set onto the ink/squeegee side of screen. Using a plastic applicator, spread Fast Set over all the open areas of the screen until completely filled.
- 2) Inspect the screen for defects such as heavy accumulations. Flip the screen over and smooth out the places where Fast Set may have collected on the opposite side. Leave the screen to dry in a level position. Check for pinholes by holding screen up to a light. Fill any pinholes with Fast Set and allow to dry completely.
- 3) When printing is done, remove ink with Bio-1 or other approved Kor-Chem ink remover. To remove blackout, rinse the screen with water and use soft nylon bristle brush on both sides of screen to thoroughly clean.

TYPICAL PRODUCT PROPERTIES

Appearance ----- Opaque blue liquid
Odor----- None
pH -----5.0
Specific Gravity ----- 0.95
Weight, per U.S. gallon -----7.9 lbs.
Stability ----- Stable
DOT Shipping ----- Non-hazardous

AVAILABLE PACKAGE SIZES

55 Gallon Drum -----#01448-D5505
5 Gallon Pail ----- #01448-P5010
4x1 Gallon Case -----#01448-C4002
12x1 Quart Case ----- #01448-C3102

