

# ER-1-2-5

## concentrated emulsion remover with degreaser

### DESCRIPTION

ER-1-2-5 is a concentrated emulsion remover formulation designed for fast removal of emulsions and capillary films from screens by means of spray or wipe-on application. ER-1-2-5 has degreasers built in to eliminated additional steps in the reclamation process.

### ADVANTAGES

- Fast removal of hardened emulsions
- Drain safe
- Contains No VOCs
- Biodegradable
- Non-Hazardous
- Concentrated for maximum economy

### DIRECTIONS

This container of ER-125 can be diluted from 1:2 to 1:5 (chemical:water) depending on emulsion type and method of application. After determining proper ratio for your needs, mix contents in plastic container and fill with appropriate amount of water.

Spray on ER-1-2-5 in a uniform pattern onto the print contact side of the screen. In some cases better results are obtained by applying ER-1-2-5 onto both sides of the screen. Allow to stand up to 3 minutes depending on the type and hardness of the emulsion. Remove the emulsion using a medium to high pressure cold water rinse. Flush the screen with a final rinse to remove any trace chemicals left on the screen. Allow to dry completely before recoating.

### TYPICAL PRODUCT PROPERTIES

Appearance ----- Clear, colorless liquid  
Odor----- None  
pH -----3.5  
Flash Point ----- None  
Specific Gravity ----- 1.10  
Weight, per U.S. gallon -----9.2 lbs.  
Stability ----- Stable  
DOT Shipping ----- Non-hazardous

### AVAILABLE PACKAGE SIZES

55 Gallon Drum -----#01484-D5505  
30 Gallon Drum -----#01484-D3004  
5 Gallon Pail ----- #01484-P5010  
4x1 Gallon Case -----#01484-C4201

