

ER-190

super concentrated emulsion remover

DESCRIPTION

ER-190 is a super concentrated emulsion remover designed to be fast, efficient and environmentally friendly. This aggressive, non-caustic cleaner attacks and easily remove emulsions and capillary films from screens. Formulated with powerful degreasing and wetting agents to eliminate extra steps and leave the screen degreased and ready to use. ER-190 is very economical due its high concentration which translates into significant cost savings. ER-190 is environmentally friendly, biodegradable and contains no VOC's.

ADVANTAGES

- Fast Acting
- Drain safe
- Biodegradable
- Contains No VOCs
- Fast removal of hardened emulsions
- No Odor

DIRECTIONS

This container of ER-190 can be diluted from 1:45 to 1:90 (chemical:water) depending on emulsion type and method of application. After determining proper ratio for your needs, mix contents in plastic container and fill with appropriate amount of water.

Spray on ER-190 in a uniform pattern onto the print contact side of the screen. In some cases better results are obtained by applying ER-190 onto both sides of the screen. Allow to stand for 30 seconds to 3 minutes depending on the type and hardness of the emulsion. Remove the emulsion using a medium to high pressure cold water rinse. Flush the screen with a final rinse to remove any trace chemicals left on the screen. Allow to dry completely before recoating.

TYPICAL PRODUCT PROPERTIES

Appearance ----- Clear, colorless liquid
Odor----- None
pH -----<1.5
Flash Point ----- None
Specific Gravity ----- 1.46
Weight, per U.S. gallon ----- 12.2 lbs.
Stability ----- Stable
DOT Shipping ----- Corrosive (Gallons)
LTY QTY (8 fl. oz.)

AVAILABLE PACKAGE SIZES

4x1 Gallon Case -----#01486-C4502
20x8 fl. oz. Case ----- #01486-C0805

