



# Fagor Kore 700 Series Bench Top Gas Chargrill B-G7051

### **Quick Overview**

- Cooking grease and a tray to store it.
- Machines are fitted with removable 130 mm high guards to prevent splashes, made of stainless steel.
- Stainless steel feet with adjustable height.
- Group of two high-efficiency tubular burners (one group of two burners for halfmodule).
- Independent control for each group of burners through a safety valve with thermocouple.

### Description

Bench Top Gas Chargrill B-G7051

#### **Key Features**

- Stamped surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints and automatic welding. Hidden screws.
- Fitted with an opening to collect cooking grease and a tray to store it.
- Machines are fitted with removable 130 mm high guards to prevent splashes, made of stainless steel.
- High temperature enamelled cast iron flue protector.
- Access to the components from the front.
- Machines with IPX5 grade water protection.
- Mild steel grills, dismountable without the need for tools, in 170 mm wide sections.
- The mild steel grills are reversible, with different finishes on each side:
- Tilted and grooved with ridges for meat ·Horizontal and flat for fish and vegetables
- These grills reach a very high temperature (400 °C), meaning that the surface of the product is quickly sealed and inside it remains much juicier.
- Groups of three high-efficiency tube burners, with a radiant deflector (a group of three burners for halfsized module models, two groups for whole module models).
- Independent control for each group of burners via a safety valve with a thermocouple.
- Burners turned on using electric multispark ignition. With an access tube for manual ignition.
- The fat collection trays provide the option of adding water into them, and thanks to heat radiated from the gas burners or electrical elements, a low intensity steam is generated, causing the roast to be carried out in a humid environment.

1



# Your Shipping Specifications

Net Weight (Kg)	52
Width (mm)	400
Depth (mm)	730
Height (mm)	850
Power	25MJ/h
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice