
Baton cutter

Model SLS

- SIMPLE OPERATION
- EASY TO CHAGE CUT SIZE
- EASY TO MAINTAIN
- EASY TO CLEAN
- SAFE FOR OPERATORS
- NO SPECIAL TOOLS
 REQUIRED
- MANY CUT SIZES
- CARROTS, ZUCCHINI, CUCUMBER, POTATO,

1 / 1-3 EASTSPUR CRT KILSYTH. VIC 3137 AUSTRALIA

PH +61(0)3 9761 6252 FX +61(0)3 9761 7252 sales@summitms.com.au www.summitms.com.au



The product needs to be cut to the required length first, then loaded into the feed chamber of the baton cutter. On closing the lid the pneumatic ram is activated and a pusher block pushes the product through the cutting grid then retracts.

The lid is opened and the feed chamber filled again. The cut size is easily changed by changing the cutting grid and matching pusher block.

A safety is fitted so that the lid cannot be opened whilst the ram is in operation.

- CUTS PORTIONS INTO BATONS AT 1 PIECE PER SECOND.
- STANDARD CUT SIZES
 6; 8; 10; 12; & 15 MM BATONS
 WEDGE HEADS ALSO AVAILABLE
- MANUFACTURED FROM STAINLESS STEEL AND QUALITY COMPONENTS.
- RUGGED INDUSTRIAL BUILD FOR LONG LIFE . VERY LOW MAINTENANCE NEEDS.
- EASY TO CHANGE CUT SIZE
- Capacity: 1 piece per second
- Dimensions: 52 x 26 x 30 cm.
- Pneumatic only,
- Safety switch on lid

