



ROLLY TASKER SAILS
AUSTRALIA

Sail Solutions Australia Pty Ltd
t/a Rolly Tasker Sails Australia
ABN 87 614 262 841

HEAD OFFICE
Unit 1, 41-43 Higginbotham Rd
Gladesville, NSW 2111
Ph: Greg - 0413 705559 or Sam - 0450 636190
Email: info@rollytasksailsaustralia.com.au
Web: www.rollytasksailsaustralia.com.au

SPREADER PATCH – Fitting Instructions

Mainsail

Step 1: Hoist the Mainsail to appropriate luff tension

Step 2: Mark where the spreaders contact the sail

Step 3: Drop the sail and locate the marks

Step 4: Clean sail with Methylated Spirits and a clean rag

Step 5: Apply the spreader patch and firmly rub all over using shiny side of the backing paper to create heat. If you are supplied with two different sizes of patches for each spreader, fit the smaller patch first and then fit the larger patch over the top to create a double layer

Headsail

Step 1: Hoist the Headsail to appropriate luff tension

Step 2: Mark where the spreaders contact the sail

Step 3: Drop the sail and locate the marks


Step 4: Clean sail with Methylated Spirits and a clean rag

Step 5: Position the patch over the mark and try keeping the patch parallel to the deck line. Then fold and trim the longest edge around the leech to ensure secure and neat fit

Step 6: Apply the spreader patch and firmly rub all over using the shiny side of the backing paper to create heat

Note: Never fit patches to wet or dirty sails.

Mainsail Patch



Headsail Patch

