

NUTECH QUICK REFERENCE ROOF COATING GUIDE

Product	Thinning	Compatible with	Recoat @ 25°C	Uses	Additional	Spread rate	Tip Size
Primers:							
NuPrime	No Dilution	All roof top coats	2 hours	Powdery oxidised roof tiles and paint	Saturation coating milky dries clear	1 coat @ 4m ² /L	519-521
SupaPrime	No Dilution	All roof top coats	2 hours	Powdery oxidised roof tiles and paint	Saturation coating milky dries clear	1 coat @ 4m ² /L	519-521
Master Sealer	No Dilution	All roof top coats	2 hours	Stable cement roof tiles and paint	Saturation coating milky dries clear	1 coat @ 4m ² /L	519-521
NuBond	No Dilution	All roof top coats	4 hours	Newer, shiny roof tiles	Milky dries clear	1 coat @ 4m ² /L	519-521
FlexiPrime	No Dilution	All roof top coats	4 hours	Unstable & previously painted surfaces	Can be tinted to most colours	1 coat @ 5m ² /L	523-525
GP Primer	No Dilution	All roof top coats	4 hours	Very rough & porous cement roof tiles	Light Grey colour	1 coat @ 4m ² /L	523-525
Metal Primer	No Dilution	All roof top coats	4 hours	Metal roofing	Light Grey colour	1 coat @ 6m ² /L	523-525
Elite Terracotta Primer	No Dilution	All roof top coats	2 hours	Raw uncoated, glazed & vitrified terracotta tiles	Milky White	1 coat @ 12m ² /L	519-521
Asbestos Sealer	No Dilution	All roof top coats	2 hours	Asbestos sheeting	Opaque White	1 coat @ 4m ² /L	519-521
Top Coats:							
NuFlex	No Dilution	All roof primers	2 hours	Trade Quality	10 year warranty	2 coats @ 4m ² /L	519-523
TileFlex	No Dilution	All roof primers	2 hours	Premium Quality	15 year warranty	2 coats @ 4m ² /L	519-523
NXT Cool Zone (gloss & low sheen)	No Dilution	All roof primers	2 hours	Ultra Premium Heat Reflective	20 year warranty	2 coats @ 4m ² /L	519-523
FlexiShield (low sheen & matt)	No Dilution	All roof primers	4 hours	Mainly for Metal Surfaces	10 year warranty	2 coats @ 5m ² /L	519-523
Other Products:							
TerraGlaze	No Dilution	Silicon modified	4 hours	Porous, unglazed terracotta & concrete tiles	Clear	2 coats @ 5m ² /L	519-521

* This is a quick reference guide only.

**Primers must be top coated.

***For complete information on all products, refer to the Nutech Technical Data Sheets, Application Guidelines and Safety Data Sheets.