

Page 1 of 12

#### **SECTION 1: IDENTIFICATION**

#### 1.1 Product identifier

Product name Aqua-Ivory 4K
Recommended use and restrictions on use

**Recommended use** For use in Phrozen 3D-printers

**Restrictions on use** Do not use in the situation that easily generate aerosol, steam.

#### 1.2 Name, address and phone of manufacturer, importers or supplier

Manufacturer Phrozen Tech Co., Ltd.287 Niupu Rd, Xiangshan Dist,

Hsinchu City 30091, TAIWAN(R.O.C)

Phone +886-3621-0505

Emergency phone / Fax +886-3621-0505 / +886-3539-6591

#### **SECTION 2: HAZARD IDENTIFICATION**

#### 2.1 Hazard classification

Skin corrosion/irritation Category 2, Serious eye damage/eye irritation Category 1,

Skin sensitization Category 1, Reproductive toxicity Category 1B,

Hazardous to the aquatic environment (acute hazard) Category 1,

Hazardous to the aquatic environment (chronic hazard) Category 2,

## 2.2 Signal statement

Corrosion, Exclamation mark, Health hazard, Environment



#### 2.3 Pictograms

#### **2.4 Signal word** Danger

#### 2.5 Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May damage fertility. May damage the unborn child

Very toxic to aquatic life with long lasting effects

Page 2 of 12

## 2.6 Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Obtain special instructions before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, If present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point.

#### 2.7 other hazard

None

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS number	Weight %	Classification acc. to GHS
4,4'-Isopropylidenediphenol, oligo meric reaction products with 1- chl oro-2,3-epoxypropane, esters with acrylic acid	55818-57-0	20 – 40%	Skin Sens. 1 / H317 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411
Oxybis(methyl-2,1-ethanediyl) diac rylate	57472-68-1	10 – 20%	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Eye Dam. 1 / H318
Glycerol propoxylate (1PO/OH) triacrylate	52408-84-1	5-20%	Acute Tox. 4 / H302 STOT RE 2 / H373 Eye Dam. 1 / H318 Skin Sens. 1 /H317
2-phenoxyethyl acrylate	48145-04-6	1-10%	Skin Sens. 1A / H317 Repr. 2 / H361d

Page 3 of 12

			Aquatic Chronic 2 / H411
Polytetrahydrofuran	25190-06-1	1-6%	Acute Tox. 4 / H302 STOT SE 3 / H336
diphenyl(2,4,6- trimethylbenzoyl)p hosphine oxide	75980-60-8	0.5- 2%	Repr. 1B / H360FD
Titanium dioxide	13463-67-7	<1%	Carc. 2 / H351
Pigment	84632-65-5	< 0.1%	-

#### **SECTION 4: FIRST AID MEASURES**

### 4.1. First-aid advice and recommendations for different routes of exposure

#### 4.1.1 Inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Incase of respiratory tract irritation, consult a physician. Provide fresh air.

#### 4.1.2 Skin Contact

Wash with plenty of soap and water.

### 4.1.3 Eyes Contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, freshwater for at least 10 minutes, holding the eyelids apart.

## 4.1.4 Ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2. Most important symptoms and hazardous effecects

None

#### 4.3. Protection of First-aid personnel

None

### 4.4. Note for physician

None



Page 4 of 12

#### **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1 Applicable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

#### 5.2 Specific hazards confronted during fire fighting

Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Specific fire-fighting procedure

None

#### 5.4 Specific protecttive equipments for fire-fighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## **6.1.** Personal precations

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

#### **6.2.** Environmental precations

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3. Cleaning methods

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur(dia tomite), sand, universal binder. Covering of drains.

Place in appropriate containers for disposal. Ventilate affected area.

#### **SECTION 7: SAFETY HANDLING AND STORAGE**

#### 7.1. Handling

Use local and general ventilation. Use only in well-ventilated areas.

Do not eat, drink and smoke in work areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Wash hands after use.



Page 5 of 12

Never keep food or drink in the vicinity of chemicals.

Never place chemicals in containers that are normally used for food or drink.

#### 7.2. Storage

Storage at the area of cool, dry.

Keep away from heat ,direct sunlight, rainy and rapid temperature .

Storage temperature between 15°C/59°C to 35°C/95°F.

Close the lid tightly when not in use.

#### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1. Engineering controls

Provide adequate ventilation to the areas where the product is stored and/or handled.

#### 8.2. Control Parameters

Component	TWA	STEL	CEILING	BEI s
Titanium dioxide	10 mg / m <sup>3</sup>	$15 \text{ mg/m}^3$	-	-

#### 8.3. Personal protective equipment

### 8.3.1 Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### 8.3.2 Hand protection

Chemical protection gloves are suitable, which are tested according to EN 374.

For example: NBR: acrylonitrile-butadiene rubber

Material thickness : ≥ 0.6mm

Breakthrough times of the glove material: > 480 minutes (permeation: level 6)

#### 8.3.3 Eye protection

Use safety goggles.

#### 8.3.4 Skin protection

Use clothing that provides complete protection to the skin.

#### 8.4. Hygiene measures

Do not eat, drink and smoke in work areas.

Wash thoroughly after handling.

Keep clean of operation area.

Take off polluted clothing as soon as possible after work. The clothing can be re-wear only after washed in clean or discard.

Page 6 of 12

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Apperance and color	Whitish viscous liquid	Odor	Typical acrylate
Odor threshold	N/A	Melting point	N/A
pH value	7	Boiling point	104.5 °C at 2.05 hPa
Flammable	N/A	Flash point	N/A
Decomposition Temp	N/A	Testing method	N/A
Natural Temp	240°C	Explosive limit	N/A
Vapor pressure	0.5 hPa at 86.6 °C	Vapor density	N/A
Density	1.12 g /cm³ at 20 °C	Solubility	N/A
Octanol/water distrib ution coefficient (log Kow)	N/A	Evaporaion rate	N/A

## **SECTION 10: STABILITY AND REACTIVITY**

## 10.1. Stability

Stable under normal condition.

## 10.2. Possible hazardous reation under specific conditions

None

#### 10.3. Must avoid condition

UV-radiation/sunlight.

### 10.4. Must avoid substances

Oxidisers, Reducing agents

## 10.5. Hazardous decomposted product

None

Page 7 of 12

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Information on toxicological effects

Test data are not available for the complete mixture.

## 11.1. Exposure paths

None

#### 11.2. Symptoms

None

#### 11.3. Acute toxicity

Components	route	Species	End point	Value
Polytetrahydrofuran	Oral	Rat	LC50	>3.4ppm/4H
	Ingetion	Rat	LD50	>5000mg/l
Diphenyl(2,4,6-trimethyl	Oral	Rat	LD50	> 5,000 mg/kg
benzoyl)	Dermal	Rat	LD50	> 2,000 mg/kg
phosphine oxide				
Titanium dioxide	Oral	Rat	LD50	>10000 mg/kg
	Dermal	Rat	LD50	>10000 mg/kg
	Ingetion	Rat	LC50	>5.09 mg/l/4h

## 11.4. Chronic toxicity

None

## 11.5. Reproductive and/or Developmental Effects

Components	route	Species	End point	Value
Diphenyl(2,4,6-trim	Ingestion	Rat	NOAEL	200 mg/kg/day
ethyl benzoyl)			premating into	
phosphine oxide			lactation for female	

## **SECTION 12: ECOLOGICAL INFORMATION**

The product has not been tested. The statement has been derived from the properties of the individual components.



Page 8 of 12

## 12.1. Ecological toxicity

Aquatio	toxicity (acu	ite) of compone	ents of the mixture	
Components	End point	Value	Species	Exposure time
Oxybis(methyl-2,1-ethan	LC50	4.64 mg/l	fish	96 h
ediyl) diacrylate	EC50	22.3 mg/l	aquatic invertebra	48 h
			tes	
	ErC50	16.7mg/l	algae	72h
Bisphenol A epoxy	LL50	>100 mg/l	fish	96 h
diacrylate	LC50	0.082mgl	fish	96h
	EC50	>16mg/l	aquatic invertebra	48h
			tes	
	EL50	105mg/l	algae	48h
	ErC50	17mg/l	algae	72h
Trimethylolpropane	LC50	0.87mg/l	fish	96h
triacrylate	ErC50	4.86mg/l	algae	96h
	EC50	7.2mg/l	algae	72h
2-phenoxyethyl acrylate	LC50	<22mg/l	fish	72 h
	EC50	3.85mg/l	aquatic invertebra	48 h
			tes	
	ErC50	4.4mg/l	algae	72h
diphenyl(2,4,6- trimethyl	LC50	1.4mg/l	fish	96 h
benzoyl)	EC50	3.53mg/l	aquatic invertebra	48 h
phosphine oxid			tes	
' '	ErC50	>2.01mg/l	algae	72h
Aquatic	toxicity (chro	nic) of compon	ents of the mixture	
Components	End point	Value	Species	Exposure time
Oxybis(methyl-2,1-ethan	EC50	>1,000 mg/l	microorganisms	30 min
ediyl) diacrylate				
Bisphenol A epoxy	EC50	>1,000 mg/l	microorganisms	3h
diacrylate				
2-phenoxyethyl acrylate	EC50	177mg/l	microorganisms	3h
Diphenyl(2,4,6-trimethyl	EC50	>1,000 mg/l	microorganisms	180 min
benzoyl)				
phosphine oxide				

Page 9 of 12

## 12.2. Per sistence and degradability

Degradability of components of the mixture				
Components	Process	Degradation rate	Time	Source
Oxybis(methyl-2,1-et	DOC removal	90–100 %	28d	ECHA
hanediyl) diacrylate				
Bisphenol A epoxy	oxygen	42%	28d	ECHA
diacrylate	deple-tion			
Trimethylolpropane	carbon	82 - 90%	28d	ECHA
triacrylate	dioxide			
	generation			
2-phenoxyethyl	oxygen	22.3%	28d	ECHA
acrylate	deple-tion			
Diphenyl(2,4,6-trimet	oxygen	0 -10%	28 d	ECHA
hyl benzoyl)	deple-tion			
phosphine oxide				

## 12.3. Bio-accumulative potential

Components	BCF	Log kow	BOD/COD
Oxybis(methyl-2,1-et		0.01 - 0.39 (pHvalue : 7, 24°	
hanediyl) diacrylate		C)	
Bisphenol A epoxy		1.6 – 3.8 (pHvalue : 6.4, 23°	
diacrylate		C)	
Trimethylolpropane		4.35	
triacrylate			
2-phenoxyethyl		2.58	
acrylate			
Diphenyl(2,4,6-trimet	47 – 55	3.1 (pH value: 6.4, 23 °C)	-
hyl benzoyl)			
phosphine oxide			

## 12.4. Mobility in soil

None

## 12.5. Other adverse effects

None



Page 10 of 12

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1. Waste disposal methods

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### 13.2. Sewage disposal method

Do not empty into drains. Avoid release to the environment.

## 13.3. Contaminated Packaging disposal method

Handle contaminated packages in the same way as the substance itself.

#### **SECTION 14: TRANSPORT INFORMATION**

Land transport USDOT	Not classified as dangerous goods under transport regulations.
Sea transport IMDG	Not classified as dangerous goods under transport regulations.
Air transport IATA/ICAO	Not classified as dangerous goods under transport regulations.
Further information	N/A
Other requirements	N/A

#### Additional information for IMDG CODE 3.4.1:

According to the general provisions 2.10.2.7, if the volume of the product is less than 5L or the mass is less than 5kg when transported, and the packaging complies with the general provisions in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8, the product is not regarded as dangerous goods transportation.

Page 11 of 12

#### **SECTION 15: REGULATORY INFORMATION**

- **15.1.** List of substances subject to authorisation (REACH, Annex XIV) / SVHC- candidate list None of the ingredients are listed
- 15.2. Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

None of the ingredients are listed

15.3. Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed

## 15.4. Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

#### 15.5. National inventories

Country	Inventory	Status	
AU	AU AICS	all ingredients are listed	
CA	DSL	all ingredients are listed	
CA	NDSL	all ingredients are listed	
CN	IECSC	all ingredients are listed	
EU	ECSI	not all ingredients are listed	
EU	REACH Reg.	not all ingredients are listed	
JP	CSCL-ENCS	not all ingredients are listed	
JP	ISHA-ENCS	not all ingredients are listed	
NZ	NZIoC	all ingredients are listed	
TR	CICR	not all ingredients are listed	
TW	TCSI	all ingredients are listed	
US	TSCA	all ingredients are listed	

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
DSL	Domestic Substances List (DSL)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
EU	EC Substance Inventory (EINECS, ELINCS, NLP)

Page 12 of 12

EU	REACH registered substances
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
NZIoC	New Zealand Inventory of Chemicals
CICR	Chemical Inventory and Control Regulation
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

#### **SECTION 16: OTHER INFORMATION**

Reference	US OSHA HCS 29 CFR 1910.1200
Table formulation	Name: Phrozen Tech. Co. Ltd
unit	Address / Phone : 287 Niupu Rd, Xiangshan Dist, Hsinchu City 30091,
	TAIWAN( R.O.C ) /+ 886-3-6210505
Table formulator	Job title : Occupational Safety & Health manager
	Name : Chun-Yao, Kuo
Table formulation	2023.11.14
Date	
Remarks	In the above described information, the symbol "N/A" means no
	relevant information currently.

To the best of our knowledge the information contained herein is accurate. However, Phrozen Tech. Co. Ltd. makes no warranty, expressed or implied, regarding the accuracy of these results to be obtained from the use thereof. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Phrozen Tech. Co. Ltd. assumes no responsibility for injury from the use of the product described herein.

# **END OF SAFETY DATASHEET**