

ECOCUT HSG 915LE - OPEL

Low misting neat cutting and grinding fluid.

Description

Ecocut HSG 915 LE is recommended for machining steel and non-ferrous materials. The abbreviation LE means “low evaporation” and stands for excellent anti-mist properties and additional outstanding low evaporation during use. Such oils contribute towards reducing environmental and workshop pollution.

The Ecocut HSG 915 LE is designed as a high speed grinding oil for machining drill and tap flutes as well as manufacturing circular metal saw blades using the oscillating grinding process. The optimised heat transfer properties permit higher feed and cutting speeds.

Application

- Recommended for central systems and singly filled machines too.
- Can be used on all belt type filter systems known for machine tools.
- Use as supplied.

Advantages/Benefits

- Chlorine free EP additives
- Enhances tool tip life
- Excellent corrosion protection
- Good cooling and lubrication
- Good detergent and dispersing qualities
- Low evaporation technology
- Outstanding anti-mist properties

Product Information



CHARACTERISTICS

Appearance
Density @ 15 °C
Kinematic Viscosity @ 40 °C
Flash Point, COC

Visual
DIN 51757
ASTM D445
ASTM D92

Clear, yellow liquid	N/A
0.855	Kg/L
15	cSt
165 min.	°C

Product Code: 1360
Last Update: 31/03/2016