

SAWMASTER 32

A saw and saw-guide lubricant designed for heavy duty applications requiring extra anti-wear protection and adherence.

Description

SAWMASTER 32 is a saw and saw-guide lubricant designed for heavy duty applications requiring extra anti-wear protection and adherence.

SAWMASTER 32 has proven itself in difficult areas of saws and guide lubrication where a tenacious lubricant film is required. The natural tackiness of the lubricating film allows for reduced oil consumption and maximum resistance to "fling off" from saws and guides.

Application

SAWMASTER 32 is fully miscible with conventional mineral based oils

Advantages/Benefits

- Reduced water consumption resulting in drier sawdust and chips
- High degree of tackiness prevents "fling off" from moving parts and provides consistent lubricating film for saws and guides
- Prevents rust and corrosion on metallic components
- Low misting
- Effective anti-wear additives provide superior protection for saws and guides against wear and scuffing
- High viscosity index ensures easier pumpability at low temperatures reducing the need for heated lines and pumping equipment
- High viscosity index ensures easier pumpability at low temperatures reducing the need for heated lines and pumping equipment

Product Information



CHARACTERISTICS

Appearance	Visual	Clear, pale amber liquid	-
Density @ 15 °C	DIN 51757		0.855 Kg/L
Kinematic Viscosity @ 40 °C	ASTM D445		35 cSt
Flash Point, COC	ASTM D92		220 typ. °C

Product Code: 2306
Last Update: 08/01/2018