

Features

- 2-way performance speaker kit which combines outstanding sound quality with versatile physical integration options
- High efficiency and 3 Ohms technology for maximized power output of the amplifier
- Smart, automotive grade connectors for fail-safe and secure installation – COMPOSE Connect & FlexConnect
- Tweeter
 - 0.75" / 20 mm tweeter with titanium dome for accurate and dynamic treble response
 - Highly efficient neodymium magnet for high magnetic flux linearity
 - Compact design and various mounting options for numerous installation demands
 - Mounting pods for flush mount and angle mount included in delivery
- Midrange
 - 4" / 100 mm midrange with unique Cenosphere coated paper cone for precise and detailed sound reproduction
 - High-tech polymer composite basket reinforced with glass beads for enormous rigidity and minimized ringing
 - Shallow neodymium magnet system for low installation depth and high efficiency
 - Polyurethane dustcap for optimized frequency response in the upper midrange area
- Crossover
 - Separate, high-grade crossover with compact dimensions for easy integration
 - 6-stage tweeter level adjustment with integrated tweeter protection for optimized treble adaptation to mounting position
 - Extensively fine-tuned – with 12 dB slope for the tweeter
 - Designed for optionally available, car-specific WireKits which allow a non-destructive integration
- Designed for the optionally available car-specific FlexMount100 & FlexMount20 adaptors which allow an acoustically optimized and professional integration in the original mounting locations of the vehicle