

## IR Illuminators for Digisight Ultra

### Ultra-X940 IR Illuminator TECHNICAL SPECIFICATIONS

<b>Diode type</b>	LED
<b>Lens diameter, mm</b>	32
<b>IR wavelength, nm</b>	940 -invisible
<b>Range of beam divergence, degree</b>	5.5-6.5
<b>Mount type</b>	Digisight Ultra
<b>Waterproof rating</b>	IPX7 - waterproof
<b>Body material</b>	Plastic
<b>Operating Temp, °F / °C</b>	-13 - 104 / -25 - 50
<b>Dimensions (mm)</b>	103 x 38 x 36
<b>Weight (oz.)</b>	4.6



#### FEATURES

- Designed for use with Digisight Ultra N455, N450, N230
- High powered LED IR illuminator
- Increases detection and identification range
- Variable beam control, from spot to flood
- Adjustable IR, position beam within the field of view
- Variable output power (brightness)

### Ultra-X850 IR Illuminator TECHNICAL SPECIFICATIONS

<b>Diode type</b>	LED
<b>Lens diameter, mm</b>	32
<b>IR wavelength, nm</b>	850
<b>Range of beam divergence, degree</b>	5.5-6.5
<b>Mount type</b>	Digisight Ultra
<b>Waterproof rating</b>	IPX7 - waterproof
<b>Body material</b>	Plastic
<b>Operating Temp, °F / °C</b>	-13 - 104 / -25 - 50
<b>Dimensions (mm)</b>	103 x 38 x 36
<b>Weight (oz.)</b>	4.6

#### INCLUDED ACCESSORIES

- Carrying case
- Cleaning cloth

**PL79135 & PL79136**