PULSAR

Ultra-850
IR Illuminator

TECHNICAL SPECIFICATIONS

Equivalent IR Power (mW)	200
Diode Type	LED
Lens Diameter (mm)	24
IR Wavelength (nm)	850
Power Supply	N/A
Range of Beam Divergence (degree)	5.5 - 6.5
Rifle Mount	Attaches to Digisight Ultra
Battery Life (hour)	N/A
Waterproof Rating	IP55 - water resistant
Body Material	Plastic
Operating Temperature (°F / °C)	-13 - 104 / -25 - 50
Length (in/mm)	4.3/109
Width (in/mm)	1.8/45
Height (in/mm)	1.4/36
Weight (oz)	3.03

FEATURES

- Designed for use with Digisight Ultra models
- High powered LED IR illuminator
- Increases detection and identification range
- Variable beam control, from spot to flood
- Adjustable IR, position beam within the field of view
- Variable output power (brightness)

INCLUDED ACCESSORIES

- Carrying case
- Cleaning cloth
- User manual

ABOUT

Designed specifically for Digisight Ultra models, the Ultra-850 IR Illuminator attaches directly to the side socket of the Digisight Ultra's housing. Useful for those trying to increase their night time detection and identification range, this IR features variable beam control able to focus from spot to flood. The Ultra 850-IR Illuminator is also adjustable to position the beam within the scope's field of view and has 3 different variable brightness settings.

PL79137