



IPS7 BATTERY PACK PL79166 TECHNICAL SPECIFICATIONS

Battery Type	Li-Ion
Rated Capacity (MilliAmpere-hour Rating), mAh	6,400
Charge voltage, V	5
Rated voltage, V	3.7
Rated charge current, A	1.3
Operating charge current, A	< 2
Full charge time, hour	5
Full discharge time (with Helion), hour	10-13
Body material	Glass-nylon composite
Operating temperature (F/C)	-4 to 140 / -20 to 60
Length, in/mm	2.9 / 73
Width, in/mm	1.7 / 47
Height, in/mm	1.2 / 30
Weight, oz	4.6

FEATURES

- Rechargeable lithium-ion battery
- Designed to power Digisight Ultra, Forward, Helion, and Trail products

INCLUDED ACCESSORIES

- Protective cover

IPS14 BATTERY PACK PL79168 TECHNICAL SPECIFICATIONS

Battery Type	Li-Ion
Rated Capacity (MilliAmpere-hour Rating), mAh	12,800
Charge voltage, V	5
Rated voltage, V	3.7
Rated charge current, A	1.3
Operating charge current, A	< 2
Full charge time, hour	10
Full discharge time (with Helion), hour	21 - 26
Body material	Glass-nylon composite
Operating temperature (F/C)	-4 to 140 / -20 to 60
Length, in/mm	2.9 / 73
Width, in/mm	1.7 / 47
Height, in/mm	2 / 50
Weight, oz	8.5

FEATURES

- Rechargeable lithium-ion battery
- Designed to power Digisight Ultra, Forward, Helion, and Trail products

INCLUDED ACCESSORIES

- Protective cover

PL79166 - PL79168