



SS Stainless Steel

4 Type

- A** Mounting from the back (tapped blind hole)
- B** Mounting from the operator's side

Specification



- Stainless steel
 - Type A: European Standard No. 1.4301 (AISI 304)
 - Type B: fine die-cast European Standard No. 1.4308 (AISI CF-8)
 - Matte shot-blasted finish **GS**
 - Slip polished, glossy metallic finish **GP** (only Type A in metric sizes)

- RoHS compliant

On request

- Special lengths
- Various inch and metric size fasteners and kit packaging

Information

GN 565.5 cabinet "U" handles are often used in the food industry or other such applications where a non-corrosive material is necessary. The shape of this sturdy handle has good ergonomic features.

Type A cabinet "U" handles are manufactured from a bent aluminum profile. The manufacturing process allows the production of special lengths in relatively small quantities.

For type B, in addition to using metric fasteners for mounting, 10-24 socket cap screws can be used.

see also...

- Cabinet "U" Handles GN 565 (Aluminum)
- Cabinet "U" Handles GN 426.5 (Stainless Steel)
- Cabinet "U" Handles GN 425 (Stainless Steel)
- "Economical" Cabinet "U" Handles GN 728.5 (Stainless Steel, Mounting from the Back or from the Operator's Side)

<p>How to order (Inch)</p> <p style="text-align: center;"> 1 2 3 4 5 </p> <p style="text-align: center; font-weight: bold;">GN 565.5-20-1/4X20-112-A-GS</p>	1	Handle width b
	2	Thread d ₁
	3	Length l
	4	Type
	5	Finish

<p>How to order (Metric)</p> <p style="text-align: center;"> 1 2 3 4 5 </p> <p style="text-align: center; font-weight: bold;">GN 565.5-20-M6-160-A-GP</p>	1	Handle width b
	2	Thread d ₁ (Bore d ₂)
	3	Length l
	4	Type
	5	Finish

Inch table

Dimensions in: inches - *millimeters*

¹ b	² d₁ Thread	³ Length l ±0.01 Type A Shot-blasted GS	a	h₁	h₂	r	t₁ min.	t₂
.79 20	1/4 x 20	4.41 112	.51 13	1.93 49	.53 13.5	.51 13	.39 10	.22 5.5
.79 20	1/4 x 20	5.04 128	.51 13	2.01 51	.53 13.5	.51 13	.39 10	.22 5.5
.79 20	1/4 x 20	6.30 160	.51 13	2.01 51	.53 13.5	.51 13	.39 10	.22 5.5

Metric table

Dimensions in: millimeters - *inches*

¹ b	² d₁ Thread	² d₂ Bore	³ Length l ±0.25			a	h₁	h₂	r	t₁ min.	t₂
			Type A Shot-blasted GS	Type A Slip polished GP	Type B Shot-blasted GS						
20 .79	M 6	5.4 .21	112 4.41	112 4.41	112 4.41	13 .51	49 1.93	13.5 .53	13 .51	10 .39	5.5 .22
20 .79	M 6	5.4 .21	128 5.04	128 5.04	128 5.04	13 .51	51 2.01	13.5 .53	13 .51	10 .39	5.5 .22
20 .79	M 6	5.4 .21	160 6.30	160 6.30	160 6.30	13 .51	51 2.01	13.5 .53	13 .51	10 .39	5.5 .22
20 .79	M 6	-	200 7.87	200 7.87	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	250 9.84	-	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	300 11.81	-	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	350 13.78	-	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	400 15.75	-	-	13 .51	51 2.01	-	13 .51	10 .39	-

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

