



Specification

- Tube Ø 30x1.5 mm
Aluminum / stainless steel
- Handle legs / covers
Plastic (Polyamide PA)
- Glass fiber reinforced
- Temperature resistant up to 212 °F (100 °C)
- Tube ● **SW**
Aluminum, powder coated
Black, RAL 9005, textured finish
Handle legs / covers
Black, matte finish
- Tube ● **EL**
Aluminum
Anodized finish, natural color
Handle legs / covers
Black, matte finish
- Tube ● **ELG**
Aluminum
Anodized finish, natural color
Handle legs / covers
Light gray, matte finish
- Tube ○ **CL**
Aluminum
White, RAL 9002, Cleanline
Handle legs / covers
White, RAL 9002, Cleanline
- Tube ● **NG**
Stainless steel
European Standard No. 1.4301 (AISI 304)
Ground, matte glossy finish
Handle legs / covers
Black, matte finish
- **RoHS compliant**

Information

GN 666 tubular grip handles offer an even more extensive size range for virtually any application that requires mounting from the bottom side.

see also...

- *Product Range Cleanline*
- *Tubular Arch Handles GN 666.4 (Aluminum / Stainless Steel, Mounting from the Back)*
- *Tubular Grip Handles GN 666.5 (Stainless Steel, Mounting from the Back)*

On request

- Various inch and metric size fasteners and kit packaging

How to order (Inch, aluminum tube)		1	Handle diameter d_1
		2	Thread d_2
		3	Length l_1
		4	Material / finish
1 2 3 4 GN 666-1.18-5/16X18-8.00-EL			
How to order (Metric, stainless steel tube)		1	Handle diameter d_1
		2	Thread d_2
		3	Length l_1
		4	Material / finish
1 2 3 4 GN 666-30-M8-500-NG			

Inch table

Dimensions in: inches - millimeters

¹ d ₁	² d ₂ SW, EL, ELG, NG	³ l ₁ ±0.02	b	h	l ₂	l ₃	l ₄	t min. 5/16X18	
1.18 30.0	5/16 x 18	8.00 203.2	.71 18.0	2.36 59.9	9.17 232.9	6.81 173.0	10.55 268.0	.59 15.0	
1.18 30.0	5/16 x 18	10.00 254.0	.71 18.0	2.36 59.9	11.18 284.0	8.82 224.0	12.56 319.0	.59 15.0	
1.18 30.0	5/16 x 18	12.00 304.8	.71 18.0	2.36 59.9	13.19 335.0	10.83 275.1	14.57 370.1	.59 15.0	
1.18 30.0	5/16 x 18	16.00 406.4	.71 18.0	2.36 59.9	17.17 436.1	14.80 375.9	18.54 470.9	.59 15.0	
1.18 30.0	5/16 x 18	20.00 508.0	.71 18.0	2.36 59.9	21.18 538.0	18.82 478.0	22.56 573.0	.59 15.0	
1.18 30.0	5/16 x 18	24.00 609.6	.71 18.0	2.36 59.9	25.20 640.1	22.83 579.9	26.57 674.9	.59 15.0	

Metric table

Dimensions in: millimeters - inches

¹ d ₁	² d ₂ SW, EL, ELG, NG	³ SW, EL, ELG, NG, CL	l ₁ ±0.5	b	h	l ₂	l ₃	l ₄	t min. M6 M8	
30 1.18	M 6	M 8	200 7.87	18 .71	60 2.36	230 9.06	170 6.69	265 10.43	12 .47	15 .59
30 1.18	M 6	M 8	250 9.84	18 .71	60 2.36	280 11.02	220 8.66	315 12.40	12 .47	15 .59
30 1.18	M 6	M 8	300 11.81	18 .71	60 2.36	330 12.99	270 10.63	365 14.37	12 .47	15 .59
30 1.18	M 6	M 8	350 13.78	18 .71	60 2.36	380 14.96	320 12.60	415 16.34	12 .47	15 .59
30 1.18	M 6	M 8	400 15.75	18 .71	60 2.36	430 16.93	370 14.57	465 18.31	12 .47	15 .59
30 1.18	M 6	M 8	500 19.69	18 .71	60 2.36	530 20.87	470 18.50	565 22.24	12 .47	15 .59
30 1.18	M 6	M 8	600 23.62	18 .71	60 2.36	630 24.80	570 22.44	665 26.18	12 .47	15 .59

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

