



SS Stainless Steel

3 Type

- A Flat spindle tip
- B Rounded spindle tip

Metric table

Dimensions in: millimeters - inches

d ₁ Thread	Length l		d ₂	d ₃	h	m	r	
	mm	inches						
M 4	33 1.30	43 1.69	-	8 .31	8 .31	10 .39	2.2 .09	6 .24
M 5	45 1.77	55 2.17	-	10 .39	9 .35	11 .43	2.7 .11	8 .31
M 6	35 1.38	55 2.17	65 2.56	13 .51	12 .47	12 .47	3.2 .13	10 .39
M 8	43 1.69	68 2.68	-	16 .63	14 .55	18 .71	4 .16	12 .47
M 10	50 1.97	77 3.03	97 3.82	20 .79	18 .71	21 .83	5 .20	15 .59
M 12	100 3.94	130 5.12	-	25 .98	23 .91	24 .94	6 .24	18 .71

Specification

- Spindle
 - Steel **ST**
 - Zinc plated, blue passivated finish
 - Stainless steel **NI**
 - European Standard No. 1.4301 (AISI 304)
- Hexagon nuts ISO 4035
 - Steel
 - Zinc plated, blue passivated finish
 - Stainless steel
 - European Standard No. 1.4301 (AISI 304)
- Spindle tip
 - Rubber, Neoprene (CR)
 - 85 shore A ≈
 - Vulcanized
 - Black
- **RoHS compliant**

Information

GN 708.1 toggle clamp spindle assemblies are primarily used with toggle clamps. They provide non-marking, yet secure clamping or holding of the work piece via the toggle clamp. The hexagon nuts are included.

see also...

- *Clamp Mounts GN 801 (for Toggle Clamps with Solid Clamping Arm)*
- *Clamp Mounts GN 809 (for Toggle Clamps with Forked Clamping Arm)*

How to order (Steel)	1 Thread d ₁
	2 Length l
GN 708.1-M4-33-A-ST	3 Type
	4 Material

How to order (Stainless steel)	1 Thread d ₁
	2 Length l
GN 708.1-M8-43-B-NI	3 Type
	4 Material