



Metric table

Dimensions in: millimeters - *inches*

¹ d ₁ Thread	² Length l				d ₂	e	h	m
M 5*	37 1.46	-	-	-	14 .55	-	10 .39	4.7 .19
M 6	32 1.26	42 1.65	52 2.05	-	12 .47	2.2 .09	7 .28	5.2 .20
M 8	38 1.50	48 1.89	63 2.48	83 3.27	16 .63	3 .12	9 .35	6.8 .27
M 10	44 1.73	54 2.13	64 2.52	84 3.31	20 .79	3.6 .14	11 .43	8.4 .33
M 12	55 2.17	65 2.56	85 3.35	105 4.13	25 .98	4.5 .18	13 .51	10.8 .43

* Clamping bolt M5: bolt end and thrust pad are not hardened and not removable.

Specification

- Grub screw DIN 6332
Steel, blackened finish
- Thrust pad DIN 6311
Steel, blackened finish
- Hexagon nuts ISO 4032 / DIN 934
Steel
Zinc plated, blue passivated finish
- RoHS compliant

Information

GN 802 toggle clamp spindle assemblies with swivel thrust pads are primarily used with toggle clamps. A snap ring between the screw and thrust pad provides a fast and simple connection. Thrust pad can be disassembled from screw.

see also...

- *Clamp Mounts GN 801 (for Toggle Clamps with Solid Clamping Arm)*
- *Clamp Mounts GN 809 (for Toggle Clamps with Forked Clamping Arm)*

How to order ¹ ² GN 802-M8-48	1 Thread diameter d ₁
	2 Length l