Expander Sealing Plugs- body from case-hardened steel 22880.0006



Product Description

Expander[®] sealing plugs are used for safe, quick and economic sealing of bore holes in fluid technology, e.g. hydraulic drilling holes in jig and fixture construction. Assembly is effected by pressing in the sealing plug into the drilling hole by means of the prescribed setting die. **Please refer to the technical data following these product information pages.**

Material

Body

Ball

 Case-hardened steel, zinc-plated, thick-film passivated


· Roller bearing steel, heat-treated, tempered


More information


Further products

Setting Dies, for Expander® Sealing Plug

Drawing







Order information

| | Ĩ | Art. No. | | | | | | | |
|------|----------------|---------------------|-------------------------------|--------------------|------------|------------------|-----|-----|------------|
| d1 | I ₁ | l ₂ ~ | d ₂ +0,1 | d ₃ max. | l₃ min. | x ±0,2 | S | - | |
| [mm] | | | | | | | | | |
| 6 | 6,5 | 8,6 | 6 | 5,3 | 6,3 | 0,4 | 2,5 | 1,3 | 22880.0006 |

Application example

| Working and control pressures for Expander® sealing plug, sleeve from case hardened steel 1.0403 | | | | | | | | | | | | |
|--|----------------------|-----------------|-------------------|--------------------|-------------------|--------------------|---------------------|--|--|--|--|--|
| basic material | ETG-100 AISI 1144 | C15Pb 1.0403 | GG-25 DIN 1691 | GGG-50 DIN 1693 | AlCuMg2 3.1354 | AIMgSiPb 3.0615 | G-AlSi7Mg 3.2371 | | | | | |
| | p [bar] | | | | | | | | | | | |
| d ₁ | 350 | 350 | 350 | 350 | 350 | 320 | 320 | | | | | |
| 4-10 mm | pTest [bar] | | | | | | | | | | | |
| | 1100 | 1100 | 1100 | 1100 | 1100 | 1000 | 1000 | | | | | |
| | p [bar] | | | | | | | | | | | |
| d ₁ | 280 | 280 | 280 | 280 | 280 | 250 | 250 | | | | | |
| 12-22 mm | pTest [bar] | | | | | | | | | | | |
| | 900 | 900 | 900 | 900 | 900 | 800 | 800 | | | | | |