# **Spherical Washers / Conical Seats** DIN 6319 23050.0042

#### **Product Description**



## **Material**

#### Spherical washer

Case-hardened steel, case-hardened, manganese phosphate treated

#### **Assembly**


Conical seats form D are to be used only for plain, closed round areas. For larger holes only use form G!


#### More information


#### **Further products**

- Spherical Washers / Conical Seats, similar to DIN 6319, stainless steel
- Fixture Nuts, DIN 6330 (height 1,5 d)

### **Drawing**









picture 1

picture 2

picture 3





#### **Order information**

Dimensions						For pin	For screws	Load capacity	Torque for screwed	I	Art. No.
d <sub>1</sub>	d <sub>3</sub>	h₁	h <sub>2</sub>	h <sub>4</sub>	r <sub>1</sub>	d <sub>6</sub>	d <sub>6</sub>	for static load	connections <sup>1)</sup>		
H13				with conical seat form D				max.	max.		
[mm]						[mm]	[mm]	[kN]	[Nm]	[9]	
spherical washers from case-hardened steel, form C – picture 1											
43	78	6,5	17	29	58	42	M42	542	3802	310	23050.0042

 $<sup>^{1)}</sup>$  Torques of screws 8.8, eventual pre-loads to be conisdered, coefficient of friction  $\mu_{total}$  0,14.



www.halder.com Page 1 of 2 Published on: 13.12.2018

# **Application example**



Erwin Halder KG

www.halder.com