Height Adjusting Elements 25120.0046



Product Description


For levelling of machines and installations.


For vertical adjustment, the self-locking height adjusting elements are fitted with a fine-pitch thread. All elements have a throughgoing bore for fastening purposes. A turn-out lock serves as height limit for the maximum adjustment height.

Material

· Heat-treated steel, zinc-plated by galvanization, chromalized

Drawing






Order information


| Dimensions | | | | | Stroke | For screw | Load capacity | Carrying force | I | Art. No. |
|----------------|----------------|----------------|----------------|----------------|----------------|-----------|-----------------|----------------|-----|------------|
| d ₁ | d ₂ | d ₃ | l ₁ | l ₂ | l ₃ | | for static load | max. | _ | |
| | | - | ~ | ~ | ~ | | max. | | | |
| | | [mm] | ı | | [mm] | [mm] | [kN] | [kN] | [g] | |
| 33 | 70 | M50 x 1,5 | 33 | 43 | 10 | M30 | 330 | 53 | 640 | 25120.0046 |

Accessories

| For height adjusting element size d ₂ | Dimensions of sickle spanner DIN 1810, form A | ĭ | Art. No. | | | | | | | |
|--------------------------------------------------|-----------------------------------------------|-----|------------|--|--|--|--|--|--|--|
| [mm] | [mm] | [g] | | | | | | | | |
| Sickle spanner for vertical adjustment | | | | | | | | | | |
| 70 | 68 – 75 | 253 | 25120.0985 | | | | | | | |

Application example







www.halder.com Page 1 of 1 Published on: 12.4.2019