# **Height Adjusting Elements.** high

## 25120.0106



### **Product Description**


For levelling of machines and installations.


For vertical adjustment, the self-locking height adjusting elements are fitted with a fine-pitch thread. All elements have a throughgoing bore for fastening purposes. A turn-out lock serves as height limit for the maximum adjustment height.

#### Material

Heat-treated steel, zinc-plated by galvanization, chromalized

## **Drawing**






#### **Order information**


Dimensions					Stroke	For screw	Load capacity	Carrying force	I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d₃	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>		for static load	max.	_	
			~	~	~		max.			
[mm]				[mm]	[mm]	[kN]	[kN]	[g]		
6,6	25	M15 x 1	28	43	15	M6	40	30,7	68	25120.0106

#### **Accessories**

For height adjusting element size d <sub>2</sub>	Dimensions of sickle spanner DIN 1810, form A	ĭ	Art. No.					
[mm]	[mm]	[g]						
Sickle spanner for vertical adjustment								
25	25 – 28	45	25120.0981					

#### **Application example**





Erwin Halder KG



www.halder.com Page 1 of 1

Published on: 12.4.2019