

BA28

Portable Busking and Music System

Technical Specifications

BA28	
Max. SPL peak @ 10% THD	123 dB half-space
Frequency response	+/- 3 dB, 65 Hz - 18 kHz
Frequency response	-10 dB, 55 Hz - 20 kHz
Power output	60 W Class D
Total battery operating time	Up to 12 h (with two fully charged battery packs)
Active protective circuits	Peak and RMS level limiter (one for HF and LMF each)
LMF woofer	1x 8", 1" voice coil
HF driver	1", 1" voice coil
Dispersion	70° x 70°
Active Crossover Frequency	2.5 kHz
Audio Input	2x combo XLR/ 1/4" (6.3 mm) TRS jack (Mic/Line/Inst.) 1x 1/4" (6.3 mm) TS jack (Guitar) 1x stereo 1/8" (3.5mm) mini jack (Aux)
Audio Output	1x unbalance stereo 1/8" (3.5mm) mini jack (Aux)
EQ Controls	2-band EQ for all input channels
Celestion Impulse Response (IR)	- Celestion Greenback - Celestion Blue - Celestion Vintage 30
Bluetooth	5.0
Angles up	33°
Handles	Metal Grip
Housing	MDF
Finish	Grey acrylic enamel
Front grille	1.5 mm metal grille
Pole cup	35 mm
Dimensions (WxHxD)	26.9 x 42.2 x 28.9 cm
Weight	8.5 kg / 18.7 lbs

Battery	
Battery capacity	5,200 mAh
Dimensions (WxHxD)	8 x 3 x 8.3 cm
Weight	0.25 kg / 0.6 lbs
Charging time in BA28	Around 5 hours
Charging time in optional quick charger	Around 2 hours