





XPON ONU WITH VOICE

BL-MX102LV

FEATURES

XPON 1GE+1FE+ 1POTS ONU

Plug and play, features auto-detecting, auto-configuration,

and auto firmware upgrade.

LAN Interface: 1x10/100/1000Mbps & 1x10/100Mbps auto adaptive Ethernet interfaces.



Compatible with all network and OLTs



TR-069 Technology



support IPV4 and IPV6 dual stack



Integrated Line testing Compliant with GR-909 on POTS



Support QinQ VLAN Function



Support NAT and Firewall Function



TECHNICAL SPECIFICATION

Technical item	XPON ONU with Voice [1GE+1FE+1POTS]
PON interface	1 E/GPON port
	wavelength: Tx1310nm, Rx 1490nm
	SC/UPC connector
	Receiving sensitivity :< 28dBm
	Transmitting Optical power 20KM
LAN Interface	1x 10/100/1000Mbps and 1x 10/100Mbps auto adaptive
	Ethernet Interface. Full/Half, Rj45 Connector
POTS Interface	1 FXS, Rj11 Connector
	Support G.711/G.723/G.726/G.729 codec
	Support T.30/T.38/G.711 Fax mode, DTMF Relay
	Line testing according to GR-909
LED	For Status of Power, PON, LOS, Phone, INTERNET, LAN1, LAN2
Operating Condition	Temperature 0°C ~+50°C
	Humidity 10%~90% (non-condensing)
Storing	Temperature 0°C~+60°C
	Humidity 10%~90% (non-condensing)
Power Supply	DC 12V, 1A, 1.5A
Power Consumption	110MMx90mmx25mm(LxWxH)



