

# RAZOR 200 PULSE MIG/TIG/STICK Welder

## Single & Double Pulse MIG

Pulse welding reduces the heat and minimises spatter, without compromising penetration, so it perfect for thin and soft materials like aluminium.

A single pulse weld alternates between a peak current and a background current. Double pulse welding works the same way, but with a second background current to add even more control over the arc.

- Reduced heat input, so you can weld thinner than standard MIG, perfect for aluminium
- ✓ Weld faster than a TIG weld, but with the same aesthetic appearance of TIG
- ✓ Spatter free welding, cutting your clean-up time to nothing
- ✓ Great penetration even with lower heat

## 5" LCD Touch Screen Display

Choosing your weld parameters or changing your settings mid weld has never been easier. The large touch screen display is clear, with an easy to navigate interface. You won't even need a manual to work it out.

## **Over 100+ Synergic Programs**

With over 100 preset synergic programs, setting up for a weld has never been faster. Just select your metal, wire size, and gas, and you're good to go.

#### **Hot Start and Crater Fill**

Hot Start gives you a boost in current at the start of your weld, eliminating issues with starting on cold metal, and makes welding on thicker materials and aluminium easier.

Crater Fill ramps your welding current and voltage down at the end of a weld, so you can fill in the end of a weld at a lower power, eliminating craters and pinholes.

Crater Fill and Hot Start functions on MIG, TIG and STICK mean your welds start strong and end just as strong.

#### **4 Geared Wire Drive**

With four geared wire drive rollers, you will get a more consistent and smoother wire feeding experience.

The internal housing also features storage space for additional rollers, so they're always in reach. It also comes with an internal spool light, for max visibility in any lighting.

### **High Frequency DC TIG**

You can maintain complete control over your TIG welds with the RAZOR 200 PULSE. The high frequency DC TIG welding mode comes with a full set of adjustable parameters, like pre- and post-flow, up and down slopes, as well as all things pulse. Everything you need, right at your fingertips.

## STICK (MMA)

You'll be able to STICK weld anything, including cellulosic electrodes, plus with the addition of Anti Stick, you'll never struggle to strike an arc again.

The Arc Force function helps to keep the arc stabilised throughout the weld, so it won't cut out, and stops the electrode from sticking.

Power Limit works to keep the amperage constant throughout the weld by preventing the voltage from exceeding the set value.

#### **GLICK Heat Control**

When using the GLICK function, set a base current, which you can switch to at any time during a weld by pressing the trigger button. GLICK is great for manual heat input control as you go.

## Job Memory (100 Jobs)

Save your favourite weld settings with the jobs function.

## **Digital Control Torch**

Adjust your amps, current and voltage right on the MIG torch itself. Plus, if you plug in a TIG torch, pressing the trigger will automatically switch you to the TIG screen and vice versa.



#### 15A Plug

Connect to any 15 AMP outlet.

#### 100mm & 200mm Spool Sizes

The RAZOR 200 PULSE can hold 0.5kg and 2kg aluminium spools, and 1kg and 5kg mild and stainless steel spools.

#### Ready to weld

Not just the welder, get everything you need to get started all in the one box. That includes a digital MIG torch and BONUS aluminium wire and torch consumables kit.

#### IP23S

The RAZOR 200 PULSE is rated IP23S, so it's protected from touch by fingers and objects greater than 12mm, and water spray less than 60° from vertical

### **Lightweight and Portable**

Onsite or off, you can take this machine anywhere.

#### **Generator Compatible**

Going off the grid? The RAZOR 200 PULSE can be connected to a generator. We recommend one with an 11kVa.

#### 2T / 4T / SPOT

Choose between two-touch, four-touch and spot modes to maximise operator comfort on every weld.

#### **Adjustable Arc Length**

Increase or decrease your arc length while in the synergic and pulse MIG modes to suit your weld style.

#### **Inductance Control**

Change the frequency of your short circuit MIG welds with the Inductance settings, so you can choose your preferred arc characteristics

# TECHNICAL DATA



#### SKU: U11003K

- RAZOR™ 200 PULSE MIG/TIG/STICK Welder
- 3m DM26 Digital MIG Torch fitted with carbon-polyamide liner
- 3m Twist Lock Electrode Holder
- 3m 300 Amp Earth Clamp & Lead
- Twin Gauge Argon Regulator
- 1.8m Gas Hose Complete with fittings
- · Operating Manual
- 2kg 1.2mm 5356 HYPERARC Aluminium Wire
- DM26 Consumable Starter Kit

TECHNICAL DATA	
SKU	U11003K
PRIMARY INPUT VOLTAGE	240V Single Phase
SUPPLY PLUG	15 AMP
leff (A)	14.9
RATED OUTPUT	40A/16V-200A/24V
PROTECTION CLASS	IP23S
INSULATION CLASS	Н
MINIMUM GENERATOR (kVA)	11.0
DINSE CONNECTOR	35/50
STANDARD	AS/NZ60974-1
WELDS	Mild Steel, Stainless Steel, Cast Iron, Silicon Bronze, Aluminium, Copper
WARRANTY (Years)	3

MIG SPECIFICATIONS		
MIG WELDING CURRENT RANGE	40-200A	
MIG DUTY CYCLE @ 40°C	15% @ 200A, 60% @ 101A, 100% @ 78A	
MIG WIRE SIZE RANGE	0.6-1.2mm	
MIG WIRE SPOOL SIZE	1kg / 5kg	
MIG WELDING THICKNESS RANGE	1-10mm	
DRIVE ROLLER SIZE	30/22	

TIG SPECIFICATIONS		
TIG FUNCTION TYPE	High-Frequency	
TIG WELDING CURRENT RANGE	5-200A	
TIG DUTY CYCLE @ 40°C	20% @ 200A, 60% @ 116A, 100% @ 90A	
TIG WELDING THICKNESS RANGE	1-8mm	

STICK SPECIFICATIONS		
STICK WELDING CURRENT RANGE	20-180A	
STICK DUTY CYCLE @ 40°C	15% @ 180A, 60% @ 91A, 100% @ 70A	
STICK ELECTRODE RANGE	2.5-4.0mm	
STICK WELDING THICKNESS RANGE	2-12mm	

SIZE & WEIGHT		
DIMENSIONS (mm)	605x230x400mm	
WEIGHT (kg)	17kg	

MACHINE FEATURES		
WIRE DRIVE	4 Geared	
VRD	Yes	
SYNERGIC PROGRAMS	Yes	
BURNBACK ADJUSTMENT	Yes	
THERMAL OVERLOAD PROTECTION	Yes	

